













	Conventional	Elitec W1
 <p><b>Flexible application</b> Lead acid replacement Suitable for rack or cabinet using</p>		
 <p><b>Easy to install</b> Plug and play Compact and Light 1~2 persons installation</p>		
 <p><b>Excellent low temp. performance (Optional)</b> Operate at -10 C without any limitation and attenuation</p>		
 <p><b>Battery APP (Optional)</b> Real time monitoring</p>		

<b>VOLTAGE</b>	51.2V
<b>CAPACITY</b>	10 240Wh
<b>DIMENSIONS</b>	520 x 888 x 140 mm
<b>WEIGHT</b>	90 Kg
<b>CHARGE &amp; DISCHARGE CURRENT</b>	100 A
<b>COMMUNICATION PORTS</b>	RS485 / CAN
<b>SINGLE STRING QUANTITY</b>	16 Pcs
<b>WORKING TEMPERATURE</b>	0°C - 50°C
<b>STORE TEMPERATURE</b>	-20°C - 60°C
<b>IP RATING</b>	IP 67
<b>COOLING TYPE</b>	NATURAL
<b>HUMIDITY</b>	5% ~ 95% NO CONDENSATION
<b>ALTITUDE</b>	< 4 500M
<b>DESIGN LIFE</b>	15 + years 25°C
<b>CYCLE LIFE</b>	> 6, 000* 25°C
<b>CERTIFICATIONS</b>	IEC62619 / UN38.3 / CE / UKCA

