

Model		AU-1000S
Input	DC Voltage	12V or 24V or 36V or 48V
	Voltage Range	10-15VDC or 21-30VDC or 30-45VDC or 42-60VDC
	No Load Current Draw	<1A
	Efficiency	> 85%
	DC Connector	Cables With Clips or Car Adaptor
Output	AC Voltage	100/110/120VAC or 220/230/240 VAC
	Continuous Power	1000W
	Surge Power	2000W
	Waveform	Pure Sine Wave
	Frequency	50Hz or 60Hz
	AC Regulation	3%
Protection	Low Voltage Alarm	10DC±0.5V or 20.5DC±1V or 31VDC±1V or 44VDC±1V
	Low Voltage Shut Down	9.5DC±0.5V or 19.5DC±1V or 42VDC±1V
	Over Load	Shut Off Output
	Over Voltage Shut Down	15.5V or 30.5V or 45V or 61.2V
	Over Thermal	Shut Off Output Automatically
	Fuses	Short Circuit
	Environment	Working Temperature
Working Humidity		20%~90%RH non-condensing
Storage Temperature		Between -30°C and +70°C
Others	Start	Soft Start
	Cooling Ways	Cooling Fan
	Total Harmonic Distortion	THD < 5%
Pack	Machine size(mm)	281*183*92
	Packing Size(mm)	365*26*165
	Net Weight(kgs)	2.75
	Gross Weight(kg)	3.4
	Packing Type	Carton packing