



Componentes



833-R2500

Descrip. Rail 2.500 mm
UDS/CAJA 8



833-GI

Descrip. Grapa intermedia
UDS/CAJA 125



833-GF

Descrip. Grapa final
UDS/CAJA 150



833- U-01

Descrip. Unión Barra
UDS/CAJA 70



833- CTSU-01

Descrip. Unión rail Teja
UDS/CAJA 50

**** Materiales para x módulos 1 fila**

| | | 2 Módulos | 3 Módulos | 4 Módulos | 5 Módulos | 6 Módulos |
|--|--------------------|-----------|-----------|-----------|-----------|-----------|
| | 833-R2500 | 2 | 3 | 4 | 5 | 6 |
| | 833-GI | 2 | 4 | 6 | 8 | 10 |
| | 833-GF | 4 | 4 | 4 | 4 | 4 |
| | 833-U-01 | 0 | 2 | 2 | 4 | 4 |
| | 833-CTSU-01 | 4 | 6 | 8 | 10 | 10 |

Marcado
ES19/86524



Especificaciones

| | |
|----------------------------|--|
| Módulo | 2.350mm x 1.140mm |
| Superficie de anclaje | Techo de teja cerámica / hormigón |
| Materiales | Perfilería: Aluminio EN AW 6005A.T6 (Anodizado) Tornillería: Acero inoxidable A2-70 |
| Espesor del panel | De 28 a 35 mm |
| Incluye | Tornillería y junta anti goteo EPDM |
| Tornillería de anclaje | Perno acero inoxidable con junta tórica 250mm |
| Viento | Hasta 150 km/h |
| Peso estructura por módulo | 1.24kg/módulo |

Par de apriete

| | |
|------------------------|--------------|
| Tornillo Presor | 7 Nm |
| Tornillo M8 Hexagonal | 20 Nm |
| Tornillo M10 Hexagonal | 40 Nm |

Incluye



Tornillería



EPDM

WEB

