


# Himalaya G10 Series 580-600W

144-cell Bifacial HJT Half Cell  
Double-glass Solar Module



### HJT 3.0

Combining gettering process and double-sided  $\mu\text{-Si}$  to maximize cell efficiency and module power.



### -0.24%/°C Pmax temperature coefficient

More stable power generation performance and even better in hot climate.



### Small Chamfer Design

Bigger power generation area on the solar cell, increasing 1% cell power of single piece.



### SMBB design with Half-Cut Technology

Shorter current transmission distance, less resistive loss and higher cell efficiency.



### Up to 90% Bifaciality

Natural symmetrical bifacial structure bringing more energy yield from the backside.



### Sealing with PIB based sealant

Stronger water resistance, greater air impermeability to extend module lifespan.



### Higher reliability

Industrial leading product and performance warranty, ensuring modules' consistent outstanding performance.



### Suitable for Utility Solar projects

## WARRANTY

Product  
Warranty **15**  
years

Linear  
Power  
Warranty **30**  
years



ANHUI HUASUN ENERGY CO., LTD.

All rights reserved © 2020-2024

File No. HS-T2-SM-0010 Ver. 2.0 Page 1 of 2



The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Anhui Huasun reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the latest version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.


# Himalaya G10 Series 580-600W

144-cell Bifacial HJT Half Cell Solar Module

- BloombergNEF Tier 1 PV module manufacturer
- Reinsurance underwritten by Ariel Re

## Engineering Drawings

Unit: mm



## Electrical Characteristics (STC\*)

HS-182-B144	DS580	DS585	DS590	DS595	DS600
Maximum Power (P <sub>max</sub> )	580W	585W	590W	595W	600W
Module Efficiency (%)	22.45%	22.65%	22.84%	23.03%	23.23%
Optimum Operating Voltage (V <sub>mp</sub> )	45.00V	45.21V	45.42V	45.63V	45.84V
Optimum Operating Current (I <sub>mp</sub> )	12.89A	12.94A	12.99A	13.04A	13.09A
Open Circuit Voltage (V <sub>oc</sub> )	53.92V	54.12V	54.31V	54.50V	54.70V
Short Circuit Current (I <sub>sc</sub> )	13.35A	13.40A	13.45A	13.50A	13.55A
Operating Module Temperature	-40 to +85 °C				
Maximum System Voltage	DC1500V (IEC)				
Maximum Series Fuse	25A				
Power Tolerance	0~+5W				
Bifaciality	85% ± 5%				

\*STC: Irradiance 1000 W/m<sup>2</sup>, cell temperature 25 °C, AM=1.5. Tolerance of P<sub>max</sub> is within +/- 3%.

## BSTC\*\*

Maximum Power (P <sub>max</sub> )	640W	645W	650W	655W	660W
Optimum Operating Voltage (V <sub>mp</sub> )	45.00V	45.21V	45.42V	45.63V	45.84V
Optimum Operating Current (I <sub>mp</sub> )	14.23A	14.27A	14.32A	14.36A	14.40A
Open Circuit Voltage (V <sub>oc</sub> )	53.92V	54.12V	54.31V	54.50V	54.70V
Short Circuit Current (I <sub>sc</sub> )	14.73A	14.77A	14.82A	14.86A	14.91A

\*\*BSTC: Front side irradiation 1000W/m<sup>2</sup>, back side reflection irradiation 135W/m<sup>2</sup>, AM=1.5, ambient temperature 25 °C.


## Temperature Characteristics

Nominal Operating Cell Temp. (NOCT)	44 °C ± 2 °C
Temperature Coefficient of P <sub>max</sub>	-0.24%/°C
Temperature Coefficient of V <sub>oc</sub>	-0.24%/°C
Temperature Coefficient of I <sub>sc</sub>	0.04%/°C

## Safety & Warranty

Safety Class	Class II
Product Warranty	15 yrs Workmanship
Performance Warranty	30 yrs Linear Warranty*

\* Less than 1% attenuation in the 1st year, the annual attenuation from the 2nd year is no more than 0.375%, and the power is no less than 88% until the 30th year.



\* Refer to HUASUN standard warranty for details

## Mechanical Characteristics

Cell Type	HJT Mono 182 × 91.75mm
Cell Connection	144 (6 × 24)
Module Dimension	2278 × 1134 × 30 mm
Weight	32 kg
Junction Box	IP68
Output Cable	4mm <sup>2</sup> , 300mm in length, length can be customized / UV resistant
Connectors Type	MC4-Evo 2A/ PV-H4/ Z4S-abcd/ ST4
Frame	Anodised aluminum alloy
Front Load	5400 Pa
Rear Load	2400 Pa
Glass Thickness	Double glass, 2.0mm

## Shipping Configurations

Container Size	HC
Pallets Per Container	20
Modules Per Pallet (pcs)	36
Modules Per Container (pcs)	720

ANHUI HUASUN ENERGY CO., LTD.

All rights reserved © 2020-2024  
File No. HS-T2-SM-0010 Ver. 2.0 Page 2 of 2

NO.99 Qingliu Road, Economic and Technological Development Zone, Xuancheng, Anhui, China  
Tel: 0086-563-3318095 www.huasunsolar.com  
sales@huasunsolar.com customerservice@huasunsolar.com