

SPLIT PHASE HYBRID INVERTER

SE 5/6/7.6/10/11.4KHB-UL



MAXIMIZE PV INPUT POWER

- Up to 200% oversizing allowed with 3 MPPTs
- Support high power module with 30A PV input current
- Support AC coupled solar input
- Integrated arc fault circuit interrupter (AFCI) and rapid shutdown



VERSATILE APPLICATIONS

- Stackable up to 9 units
- Standby generator connection for whole-home back up
- Four application modes, mixed with time control
- Remote configuration and upgrade



FLEXIBLE BATTERY CONFIGURATION

- Built-in DC Breaker for safety and reliability
- Support 40-64V Lithium or Lead-acid battery
- Maximum battery charge/discharge current of 210A



STABLE OUTPUT POWER

- Continuous 110% of nominal AC power
- Support 120/240/208V connections
- Seamless backup transition (<10ms)



Model	SE 5KHB-130-D2/UL	SE 6KHB-130-D2/UL	SE 7K6HB-180 T2/UL	SE 10KHB-210-T2/UL	SE 11K4HB-210 T2/UL
Efficiency					
Max. Efficiency (PV to AC)	98.0%				
Max. Efficiency (BAT to AC)	94.5%				
CEC. Efficiency	96.5%				
Input (PV)					
Max. PV Input Power	7,500W	9,000W	12,000W	15,000W	15,000W
Max. PV Voltage	600V				
Start-up Voltage	90V				
MPPT Operating Voltage Range	70V-540V				
Max. Input Current per MPPT	30A/22A		30A/22A/22A		
Max short current per MPPT	40A/30A		40A/30A/30A		
String per MPPT	4 (2/2)		6 (2/2/2)		
Nos. of MPPT	2		3		
Input/Output (BAT)					
Battery Type	Lithium-ion/Lead-acid				
Nominal Battery Voltage	48V				
Battery Voltage Range	40V-64V				
Max. Charge/Discharge Current	210A/130A	210A/130A	210A/180A	210A/210A	210A/210A
Max. Charge/Discharge Power	10,000W/5,000W	10,000W/6,000W	10,000W/7,600W	10,000W/10,000W	10,000W/10,000W
Output (Grid)					
Nominal AC Output Power	5,000W	6,000W	7,600W	10,000W	10,000W
Max. AC Output Apparent Power	5,500VA	6,600VA	7,600VA	11,000VA	11,400VA
Max. AC Output Power (PF=1)	5,500W	6,600W	7,600W	11,000W	11,400W
Nominal AC Output Current	20.9A	25A	31.7A	41.7A	41.7A
Max. AC Output Current	22.9A	27.5A	34.8A	45.8A	47.5A
Nominal Grid Voltage	120V/240V (Split phase) / 208V (2/3 phase)				
Nominal Grid Frequency	50Hz /60Hz				
Grid Frequency Range	45Hz-55Hz/55Hz-65Hz (Adjustable)				
Power Factor	> 0.99 @rated power (Adjustable 0.8 LD - 0.8 LG)				
THDI	<3% (Rated Power)				
Output (Back up)					
Nominal Output Power	5,000W	6,000W	7,600W	10,000W	10,000W
Max. AC Output Power (PF=1)	5,500W	6,600W	7,600W	11,000W	11,400W
Nominal Output Current	20.9A	25A	31.7A	41.7A	41.7A
Peak Power (1s)	10,000VA	12,000VA	15,200VA	20,000VA	20,000VA
Nominal Output Voltage	120V/240V (Split phase) / 208V (2/3 phase)				
Nominal Output Frequency	50Hz/60Hz				
Transfer Time	< 10ms (typical)				
THDV	<3% @100% R Load				
Protection					
Protection Category	Class I				
DC Switch	Yes				
Anti-islanding Protection	Yes				
AC Overcurrent Protection	Yes				
DC/AC Overvoltage Protection	DC Type II, AC Type III				
AC Short Circuit Protection	Yes				
DC Reverse Protection	Yes				
Surge Arrester	DC Type II, AC Type II				
Insulation Resistance Detection	Yes				
Leakage Current Protection	Yes				
AFCI	Yes				
RSD	Yes				
Generator	Yes				
General					
Max. Operation Altitude	2000m				
Ingress Protection Degree	IP65/NEMA 3R				
Operating Temperature Range	-25 C ~60 C (>45 C derating)				
Relative Humidity	0~100%				
Cooling Method	Fan Cooling				
Mounting	Wall bracket				
Dimensions (W*H*D)	16.5*31.5*9.4 inch (420mm*800mm*240mm)				
Weight	40Kg/88lb				
PV Connection Way	Terminals				
HMI & COM					
Display	Wireless & APP + LED, LCD (optional)				
Communication Interface	RS485/CAN (for BMS), DRM/RS485 (for meter), RS485, Optional: Wi-Fi/LAN				
Certification					
Safety	UL 1741/CSA C22.2/UL 1699B				
Grid	UL1741SB, IEEE1547: 2018, HECO SRD 2.0				
EMC	FCC Part 15 Class B				
Warranty	5 Years				

Remarks: · The range of output voltage and frequency may vary depending on different grid codes.
· Specifications are subject to change without advanced notice.