

PT2000

For Emergency



MAC Pro 14 65W≈ 69.3H	iP13 Pro Max 16.75Wh≈ 269Times	Hair drier 1600W≈ 2.8H	Air conditioner 1800W≈ 2.5H
Microwave oven 1180Wh≈ 4.2H	Soybean milk machine 1000W≈ 4.9H	Electric oven 1650W≈ 2.73H	Electric drill 850W≈ 8.2H

Battery Type	LiFePO4
Battery	2880Wh / 4800Wh / 5120Wh
Cycle Life	2000 Times
USB Output	2*5V/2.4A 12W Max. 4*QC3.0 5V/3.6A, 9V/2.5A,12V/2A 24W Max. 5V/2.4A 12W Max. when two ports are used at the same time
USB-C Output	2*PD&QC3.0 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A 60W Max.
DC Output	4*12V/10A 120W Max.
CIG Output	1*12V/10A 120W Max.
AC Output	100V~120V/50Hz 60Hz 1600~1800W; Peak Power: 2600W 220V~240V/50Hz 60Hz 2000W; Peak Power: 2700W
Input	AC 1200W Max. /Car Cigar Port/Solar Panel 12~65V 20A Max. 500W (XT60)
Weight	66kg
Size	445 x 278 x 622mm, 17.51 x 10.94 x 24.48inch
Charging Temperature	0~40°C
Discharge Temperature	-10~ 40°C
Authentication certificate	CE、FCC、UL、PSE、METI、RoHs、UN38.3、MSDS、REACH

PT2000:

Constant Power

2000

Peak Power 3000W



PT3600

For Emergency



MAC Pro 14 65W≈69.3H	iP13 Pro Max 16.75Wh≈269Times	Hair drier 1600W≈2.8H	Air conditioner 1800W≈2.5H
Microwave oven 1180Wh≈4.2H	Soybean milk machine 1000W≈4.9H	Electric oven 1650W≈2.73H	Electric drill 850W≈8.2H

Battery Type	LiFePO4
Battery	2880Wh / 4800Wh / 5184Wh
Cycle Life	2000 Times
USB Output	2*5V/2.4A 12W Max. 4*QC3.0 5V/3.6A, 9V/2.5A,12V/2A 24W Max. 5V/2.4A 12W Max. when two ports are used at the same time
USB-C Output	2*PD&QC3.0 5V/3A, 9V/3A, 12V/3A, 15V/2A 30W Max.
DC Output	4*12V/10A 120W Max.
CIG Output	1*12V/10A 120W Max.
AC Output	100V~120V/50Hz 60Hz 3600W Peak Power: 5000W; 220V~240V/50Hz 60Hz 3600W Peak Power: 5000W
Input	AC 1200W Max. /Car Cigar Port/Solar Panel 12~100V 20A Max. 500W (XT60)
Weight	66kg
Size	480 x 278 x 680mm, 18.9 x 10.94 x 26.77inch
Charging Temperature	0~40°C
Discharge Temperature	-10~ 40°C
Authentication certificate	CE、FCC、UL、PSE、METI、RoHs、UN38.3、MSDS、REACH

PT3600:

Constant Power

3600

Peak Power 5800W

