

Innovation  
for A Better Life

**COSLINK** ESS

**CHANGE  
YOUR ENERGY  
PROVIDE  
ENERGY  
INDEPENDENCE**

**EnerMax-C&I**  
Distributed Battery Cabinet

[www.coslinkess.com](http://www.coslinkess.com)



## Features and Advantages



### Highly integrated

- Cluster-level intelligent management
- Support of stacking and expansion installation
- Simplified after-sales operation and maintenance



### Security

- Local EMS real-time monitoring
- Built-in aerosol firefighting system
- Reserved water firefighting interface



### Smart

- No container design, flexible site layout
- Support of multiple parallel connection

**The Leader of ESS Active Control Technology**

Green Energy: More Reliable, More Intelligent, More Economic



**UN38.3**

Model	CB215-0.5C
Nominal Capacity [Ah]	280 (25°C 0.5C discharge)
Nominal Voltage [V]	768
Nominal Energy [kWh]	215
Max. Discharge Depth	≤ 90%
Max. Continuous Charge Current [A]	140 (0.5C)
Charge Cut-Off Voltage [V]	852
Max. Continuous Discharge Current [A]	140 (0.5C)
Discharge Cut-Off Voltage [V]	696
Dimensions [W*D*H, mm]	1500*950*2200
Charging Temperature Range [°C]	0 to 45
Discharging Temperature Range [°C]	-20 to +60
Optimal Operating Temperature Range [°C]	20 to 30
Storage Humidity	60 ± 25% RH
Cooling	Smart temperature control
Communication	CAN2.0, RS485
Weight [kg]	~1950
IP Grade	IP54
Fire-Proof	Aerosol

Note: The above information may subject to update without prior notice.