

GT300/ GT600

Small, Delicate and Digital



| | | | |
|-------------------------------|--|---------------------------------|--------------------------------------|
| MAC Pro 14 65W≈7.3H | iP13 Pro Max 16.75Wh≈28Times | bulb 5W≈55H | Electric fan 40W≈11.8H |
| Projector 120W≈3.9H | Camera 8.2Wh≈55Times | Switch 16.1Wh≈29Times | Car refrigerator 30W≈15.8H |

| | |
|----------------------------|--|
| Battery Type | LiFePO4 |
| Battery | GT300: 230Wh / 256Wh / 307Wh / 384Wh; GT600: 460Wh / 576Wh / 691Wh |
| Cycle Life | 2000 Times |
| USB Output | 2*QC3.0 5V/3A, 9V/2.5A, 12V/2A 24W Max. 5V/2.4A 12W Max. when two ports are used at the same time |
| USB-C Output | 1*PD&QC3.0 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A 45W Max. |
| CIG Output | 1*12V/10A 120W Max. |
| AC Output | 100V~120V/50Hz 60Hz 300W Peak Power: 450W, 600W Peak Power: 900W 220V~240V/50Hz 60Hz 300W Peak Power: 450W, 600W Peak Power: 900W |
| Input | Charger 15V 4A 60W (5525)/Car Cigar Port/Solar Panel 12V -24V/4A Max. |
| LED Light | 3W LEDs |
| Weight | 4.3kg / 8kg |
| Size | 257 x 160 x 165mm, 10.11 x 6.29 x 6.49inch, / 298 x 174 x 197mm , 11.73 x 6.85 x 7.76inch |
| Charging Temperature | 0~40°C |
| Discharge Temperature | -10~ 40°C |
| Authentication certificate | CE、FCC、UL、PSE、METI、RoHs、UN38.3、MSDS、REACH |

GT300:

Constant Power
300
Peak Power 450W

GT600:

Constant Power
600
Peak Power 900W



GT500

Small, Delicate and Digital



| | | | |
|-------------------------------|--|--------------------------------------|------------------------------------|
| MAC Pro 14 65W≈6.8H | iP13 Pro Max 16.75Wh≈26Times | Drilling machine 250W≈1.8H | Electric fan 40W≈11H |
| Projector 120W≈3.9H | Camera 8.2Wh≈53Times | Switch 16.1Wh≈27Times | Car refrigerator 30W≈15H |

| | |
|----------------------------|--|
| Battery Type | LiFePO4 |
| Battery | 345Wh / 518Wh / 576Wh |
| Cycle Life | 2000 Times |
| USB Output | 3*5V/2.4A 12W Max. |
| USB-C Output | 1*PD&QC3.0 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A 60W Max. (Two-way) |
| Wireless charger Output | 2*10W (Optional) |
| CIG Output | 1*12V 10A 120W Max. |
| AC Output | 100V~120V/50Hz 60Hz 500W, Peak Power: 700W; 220V~240V/50Hz 60Hz 500W, Peak Power: 700W |
| Input | USB-C 60W Max./Charger 27V 4.5A 120W Max. (6514)/Car Cigar Port/Solar Panel 12V-24V 4.5A |
| LED Light & SOS | 2W LEDs |
| Weight | 7kg |
| Size | 287 x 161 x 230mm, 11.29 x 6.33 x 9.05inch |
| Charging Temperature | 0~40°C |
| Discharge Temperature | -10~ 40°C |
| Authentication certificate | CE、FCC、UL、PSE、METI、RoHs、UN38.3、MSDS、REACH |

GT500:

Constant Power
500
Peak Power 700W



GT1500

Outdoor Tooling



| | | | |
|--------------------------------|--|------------------------------------|------------------------------------|
| MAC Pro 14 65W≈15.8H | iP13 Pro Max 16.75Wh≈61Times | Coffee machine 600W≈1.7H | Rice cooker 500W≈2.1H |
| UAV 40.4Wh≈5Times | Projector 120W≈8.6H | Drilling machine 250W≈4H | Electric drill 850W≈1.9H |

| | |
|----------------------------|--|
| Battery Type | LiFePO4 |
| Battery | 1008Wh / 1209Wh / 1536Wh |
| Cycle Life | 2000 Times |
| USB Output | 3*5V/2.4A 12W Max. |
| USB-C Output | 1*PD&QC3.0 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A 60W Max. |
| CIG Output | 1*12V 10A 120W Max. |
| AC Output | 100V~120V/50Hz 60Hz 1500W Peak Power: 2000W; 220V~240V/50Hz 60Hz 1500W Peak Power: 2000W |
| Input | Charger 27V 8A 200W Max.(6530) /Car Cigar Port/Solar Panel 15V~24V 8A |
| LED Light & SOS | 2W LEDs |
| Weight | 28.5kg |
| Size | 411 x 260 x 355mm, 16.18 x 10.23 x 13.97inch |
| Charging Temperature | 0~40°C |
| Discharge Temperature | -10~ 40°C |
| Authentication certificate | CE、FCC、UL、PSE、METI、RoHs、UN38.3、MSDS、REACH |

GT1500:

Constant Power

1500

Peak Power 2000W



ST2000

For Emergency



| | | | |
|--------------------------------------|---|----------------------------|------------------------------------|
| MAC Pro 14 65W≈4.2H | iP13 Pro Max 16.75Wh≈109Times | bulb 600W≈3H | Rice cooker 500W≈3.7H |
| Microwave oven 1180Wh≈1.7H | Soybean milk machine 1000W≈2H | Kettle 800W≈2.4H | Electric drill 850W≈3.3H |

| | |
|----------------------------|--|
| Battery Type | LiFePO4 |
| Battery | 1440Wh / 2073Wh / 2160Wh |
| Cycle Life | 2000 Times |
| USB Output | 2*5V/2.4A 12W Max. 4*QC3.0 5V/3.6A, 9V/2.5A, 12V/2A 24W Max. 5V/2.4A 12W Max. when two ports are used at the same time |
| USB-C Output | 2*PD&QC3.0 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A 60W Max. |
| DC Output | 4*12V/10A 120W Max. |
| CIG Output | 1*12V/10A 120W Max. |
| AC Output | 100V~120V/50Hz 60Hz 2000W Peak Power: 2600W; 220V~240V/50Hz 60Hz 2200W Peak Power: 3000W |
| Input | AC 1200W Max. /Car Cigar Port/Solar Panel 12-65V 20A Max. 500W (XT60) |
| Weight | 28.5kg |
| Size | 411 x 260 x 355mm, 16.18 x 10.23 x 13.97inch |
| Charging Temperature | 0~40°C |
| Discharge Temperature | -10~ 40°C |
| Authentication certificate | CE、FCC、UL、PSE、METI、RoHs、UN38.3、MSDS、REACH |

