

Have sun!

On modules & mounting systems
**15 years
combination
warranty**



Ribbons

Improved light efficiency with angled light irradiation benefited by round cell connector design.



Multi-busbar technology

Reduced power and shading losses by using of 10 cell connectors.



Aesthetic design

Elegant black design for a homogeneous and high-quality appearance.

[Product datasheet](#)


IBC MonoSol 395 | 400 CS10-HC Black

Elegant black design and
high-performance in combination.

Online shop:
Find our products
and further
information here.



Have sun!



IBC MonoSol	395 CS10-HC Black	400 CS10-HC Black
Article number	2003800036	2003800035
Electrical data (STC)³		
STC Power P _{max} (Wp)	395	400
STC Nominal Voltage U _{mpp} (V)	30.37	30.56
STC Nominal Current I _{mp} (A)	13.01	13.10
STC Open Circuit Voltage U _{oc} (V)	36.74	36.87
STC Short Circuit Current I _{sc} (A)	13.43	13.55
Module Efficiency (%)	20.23	20.48
Power Tolerance (W)	-0/+5	-0/+5
Electrical data (NMOT)		
NMOT (°C)	45	45
800 W/m ² NMOT AM 1.5 Power P _{max} (Wp)	296	300
800 W/m ² NMOT AM 1.5 Nominal Voltage U _{mpp} (V)	28.69	28.89
800 W/m ² NMOT AM 1.5 Open Circuit Voltage U _{oc} (V)	34.81	34.92
800 W/m ² NMOT AM 1.5 Short Circuit Current I _{sc} (A)	11.02	11.08
Relative Efficiency Reduction at 200 W/m ² (%)	3.5	4.3
Temperature coefficient (linear)		
Tempcoeff I _{sc} (%/°C)	+0.048	+0.048
Tempcoeff U _{oc} (mV/°C)	-92.58	-92.91
Tempcoeff P _{mp} (%/°C)	-0.332	-0.332

Operating conditions	
Max. System Voltage (V)	1500
Application Class	A
Reverse Current I _r (A)	25
Fuse protection from parallel strings	2
Protection class	II (DIN EN 61140)
Fire protection	C (IEC 61730-ANSI/UL790)
Mechanical properties	
Dimensions (L × W × H in mm)	1722 × 1133 × 35
Weight (kg)	22.0
Max. Test load, Push/Pull (Pa)	5400/2400
Max. Design load ² , Push/Pull (Pa)	3600/1600
Front sheet (mm)	3.2 (low-iron photovoltaic glass and anti-reflective coating)
Frame	anodized aluminium, sturdy hollow-chamber frame
Cells	12 × 9 mono-crystalline silicon cells
Connection type	EVO2
Warranties and certification	
Product warranty	15 years ¹
Performance warranty	25 years ¹
Annual degradation	year 1 2.5% year 2-25 0.7%
Certification	IEC 61215, IEC 61730-1/-2, ISO 9001, ISO 14001, OHSAS 18001
Packaging information	
Number of modules per pallet	31
Number of pallets per truck	28
Dimensions incl. pallet (L × W × H in mm)	1760 × 1130 × 1255
Gross weight incl. double pallet (kg)	720
Stackability per pallet	2-fold

1) The linear power and product warranty are only valid for installations within Europe and Japan. The warranty requires installation according to the valid installation instructions. Standard test conditions: 1000 W/m² irradiation with a spectral distribution of AM 1.5 and a cell temperature of 25°C. 800 W/m², NOCT. Information according to EN 60904-3 (STC). All values according to DIN EN 50380. Errors and changes reserved. The precise conditions and content can be taken from the respectively valid version of the product and power warranty, which you can obtain from your IBC Premium Partner.

2) Loads according to IEC 61215-2:2016, max. design load

3) Measurement tolerances +/- 3% at STC: 1000 W/m², 25 +/- 2 °C, AM 1.5

Your Premium Partner