

Nexa Plus 480-500W

TOPCon N-type

› Black – Standard



Efficiency

Module efficiency up to 23.10 %



N-type cell

Higher resistance to LID and LeTID



TOPCon

Technology to increase cell efficiency



SuperMBB

Reduced resistance losses and improved current collection



Better temperature coefficient

Minimized thermal losses, improved efficiency



Wider irradiance range

Improved performance under dawn, sunset and cloudy skies



20 Years

Product Warranty


+5 years for Premium Partners



30 Years

Performance Warranty

Linear Warranty

88% performance at 30 years





Mechanical Specification	
Solar cells	N-Type monocrystalline silicon cells
Front Glass	3,2 mm thick tempered glass with high strength and ARC
Frame	Black/silver anodized aluminium
Junction Box	IP68, 3 by-pass diodes
Connector	Original MC4-Evo 2
Cable	1000 mm (±20%) length and 4 mm ² section
Dimension	1909 x 1134 x 30 mm (±1%)
Area	2,16 m ²
Weight and packaging	25,9 kg, 864 pcs-truck

Temperature Coefficients	
Temperature coefficient of Isc (α)	0,045 %/°C
Temperature coefficient of Voc (β)	-0,275 %/°C
Temperature coefficient of Pmax (γ)	-0,29 %/°C
Temperature range	-40 °C ~ +85 °C
Nominal operating cell temperature (NOCT)	45 ± 2 °C

	MEPV 480	MEPV 490	MEPV 500
STC: 1000 W/m², module temperature 25°C, AM 1,5			
Nominal power. Pmax	480 Wp	490 Wp	500 Wp
Module efficiency	22,18 %	22,63 %	23,10 %
Short-circuit current (Isc)	14,34 A	14,44 A	14,52 A
Open-circuit voltage (Voc)	42,63 V	42,95 V	43,25 V
Maximum power current (Imp)	13,60 A	13,78 A	13,94 A
Maximum power voltage (Vmp)	35,31 V	35,61 V	35,88 V
NOCT: 800 W/m², ambient temperature 20°C, AM 1,5			
Nominal power. Pmax	361 Wp	369 Wp	376 Wp
Short-circuit current (Isc)	11,55 A	11,69 A	11,81 A
Open-circuit voltage (Voc)	40,57 V	41,02 V	41,43 V
Maximum power current (Imp)	10,85 A	11,01 A	11,13 A
Maximum power voltage (Vmp)	33,27 V	33,48 V	33,80 V
Operating parameters			
Maximum voltage	1500 V		
Maximum series fuse rating. Ir	25 A		
Power output tolerance	0 - +3%		
Voc and Isc tolerance	±3%		
Fire rating	Class C (UL 790)		
Protection class	Class II (IEC 61140)		
Hail resistance	HW3/RG3		
Mechanical loads	Front load 5400 Pa, Back load 2400 Pa		

NOTE: Read the instruction manual of this product and follow the indications STC. Values are valid for: 1000W/m², AM 1,5 and cells temperature of 25°C. Measurement tolerance +/-3% (AAA Solar simulation -IEC 60.904-9-). All the information of this brochure may be amended without notice by Eurener.
 Eurener MEPV_NEXA Plus_480-500W_EN_APR2024



eurener.com
 contact@eurenerworld.com
 +34 960 045 515
 Calle Colón, 1-23
 46004, Valencia. Spain

Manufacturing a better world

Since 1997 our main purpose has been to supply quality and long-lasting photovoltaic modules that allow us and future generations, to continue generating clean energy to take care of our planet.