

Model E-MATE 200C



[Overview]

Outdoor battery cabinet with IP55 protection level, inbuilt lithium-ion battery and BMS

[Easy Installation And Maintenance]

Local and remote management, standard rack&module design, front maintenance

[Safety & Reliable]

Self-developed 2-level / 3-level BMS, complex protection, safe and reliable

[High Density]

LP high-capacity Li-Ion battery with aluminum shell, over 130wh/kg

[Long Lifespan]

Long cycle life, 6000 cycles

[Cell Balancing Technology]

Active cell balancing and passive cell balancing

DATASHEET

Model	E-MATE 200C
--------------	--------------------

Performance

Battery module (Wh/V)	14.3 kWh, 51.2 V, 110 kg (242.5 lbs)
Number of modules	14
Cell technology	LFP (LiFePO4)
Battery usable energy [1]	200.7 kWh
Nominal voltage	716.8 V
Operating voltage	638.4 - 786.2 V
Nominal output current	140 A / 280 A

Communication

Display	SOC status indicator, LED indicator, LCD display
Communication	Ethernet / CAN / RS485

General Specification

Dimension (W*D*H)	1050×1632×2200 mm 41.3×64.3×86.6 inch
Weight	1900 kg (4189 lbs)
Operating temperature [2]	-20 to 60 °C (-4 to 140 °F)
Environmental humidity	≤ 95%RH (No condensation)
Protection rating	IP 55
Cycle life [3]	6000 Cycles @ 80% DOD / 25°C / 0.5C, 60% EOL
Scalability	Yes
Application	ON Grid / ON Grid + Backup / OFF grid
Compatible PCS	Refer to compatible PCS list

Standard Compliance

Certificates	Cell: UN38.3 / IEC62619 / UL 1642 / JET Pack: UN38.3 / IEC62619 / IEC61000 System: UL 9540 (More available upon request)
---------------------	--

[1] Test conditions: 100% depth of discharge (DoD), 0.2C rate charge & discharge at 25°C

[2] Charge/discharge derating occurs when the operating temperature from -10°C to 5 °C & 45 °C to 55 °C

[3] Condition apply. Refer to Warranty Letter