

## **Features and Advantages**



#### **Smarter**

- Smart active control technology
- Intelligent charge & discharge control
- Integrated BMS and active control optimizer



#### **High performance**

- Cycle life: 6000 times
- Wide application temperature range
- Excellent current balancing performance
- Mixed use with lead-acid battery & conventional lithium batteries



#### **Great safety**

- Reliable LiFePO4 cells
- Multiple real-time warnings and protections
- Built-in fire-proof module



#### Compact and modular

- Standard 19" rack-mounted design (5U)
- Modular design



#### **Certification compliant**

• IEC62619, UN38.3, EN61000



#### **Smart management**

- · Local & remote monitoring
- Advanced working modes: peak shaving mode, peak shifting mode, etc.
- Precise calibration of SOC and SOH













# EnerSmart BS48V200 Li-ion Battery

| Model                                   | BS48V200   |
|---|--|
| Battery Type                            | LFP  |
| Rated Voltage [V]                       | 48   |
| Rated Capacity [Ah]                     | 220Ah@48V, 0.35C, 25°C   |
| Dimensions [W*D*H, mm]                  | 442 * 560 * 220 (without brackets)   |
| Discharging Voltage Range [V]           | 42~58 (consistent voltage)   |
| Output Power [W]                        | 3800   |
| Max. Continuous Discharging Current [A] | 70A@51.2V  |
| Weight [kg]                             | 82   |
| Cycle Life [Times]                      | 6000 times (25 °C, 0.35C, 80%DOD)  |
| Communication                           | RS485 * 2, CAN * 2, and dry contact * 2                                      |
| Parallel Connection                     | Up to 32 packs (CAN) / 16 packs (RS485)                                      |
| Balance Method                          | Passive balancing  |
| Equalizing Current [mA]                 | 100  |
| Heat Dissipation                        | Forced air cooling   |
| Working Temperature [°C]                | Charging: 0 ~ 45; discharging: -20 ~ 45                                      |
| Storage Temperature [°C]                | -30 ~ 60   |
| Relative Humidity                       | 5% ~ 95% RH (non-condensing)   |
| Protection and Alarm                    | Overheat, over-current, short circuit, over-charging, over-discharging, etc. |
| Designed Life Time                      | 15 years   |
| Working Methods                         | Constant voltage output mode   |
| Anti-Theft                              | Gyroscope  |

### **Performance Curve**





Note: The above information may subject to update without prior notice.

#### COSLINK DIGITAL ENERGY TECHNOLOGY CO., LTD.

- · Room 2A of Building 2, Winlead Intelligent Park, Shutianpu Community, Matian Sub-District, Guangming District, Shenzhen City
- +86-0755-2969 1626 sales@d
- sales@coslinkess.com