



**ECO GREEN ENERGY**  
Building a Greener World



# EGE-LiFePO<sub>4</sub> Battery 25.6V

## LITHIUM IRON PHOSPHATE BATTERY

**120Ah**

Eco Green Energy has designed its lithium iron battery series that provide versatility, durability and reliability to your On-Grid and Off-Grid Projects. Certified by international standards, our batteries offer you a wide range of options for your energy storage needs.

### FEATURES

- The whole module is non-toxic, non-polluting and environmentally friendly;
- Battery management system (BMS) has protection functions including over-discharge, over-charge, over-current, and high/low temperature;
- The cathode material is made from LiFePO<sub>4</sub> with safety performance and long cycle life;
- Small size and lightweight, comfortable for installation and maintenance;

### APPLICATIONS

- Wheelchairs and scooters;
- Back-up power for small UPS;
- Solar/wind energy storage;
- Golf trolleys & buggies;



[eco-greenenergy.com](http://eco-greenenergy.com)

## Electrical Characteristics

### 25.6V 120Ah

Nominal Voltage	25.6V
Nominal Charge Capacity	120Ah
Energy Capacity Rating	3072Wh
Internal Resistance (AC)	≤20mΩ
Cycle Life	85%DoD
Self-discharge rate	<3% per month @25°C
Efficiency rate	100% @0.5C
Discharge efficiency rate	96-99% @0.5C



EGE-25.6V 120Ah

## Charge Characteristics

Charging Voltage	28.8 ±0.2V
Charging method CC-CV	0.5C-28.8V
Recommended charging current	25A
Maximum charging current	50A
Charge Cut-off Voltage	28.8 ±0.2V

## Discharge Characteristics

Recommended discharge current	50A
Maximum discharge current	100A
Discharge Cut-off Voltage	20V

## Environmental Characteristics

Operating Temperature range	0°C to 45°C (32F to 131F) @60±25%RH
Storage Temperature range	-20°C to 45°C (-4F to 113F) @60±25%RH
IP Rating	IP65

## Mechanical

Case Material	ABS
Dimensions	522*238*218mm
Approx.Weight	24kgs
Terminal	M8

## PERFORMANCE CHARACTERISTICS

