

TECHNICAL DATA SHEET

TS HV 30-80 E

TECHNICAL DATA FOR BATTERY STORAGE SYSTEM

Product name	TS HV 30 E	TS HV 50 E	TS HV 80 E
Type designation	TS HV 50/4-20	TS HV 50/5-20; TS HV 50/6-20; TS HV 50/7-20	TS HV 50/8-20; TS HV 50/9-20; TS HV 50/10-20
Energy content (at 100% DoD)	32 kWh	40 kWh / 48 kWh / 56 kWh	64 kWh / 72 kWh / 80 kWh
Nominal voltage	324 V \approx	405 V \approx / 486 V \approx / 567 V \approx	648 V \approx / 729 V \approx / 810 V \approx
Operating voltage	290 - 365 V \approx	363 - 457 V \approx / 436 - 548 V \approx 508 - 639 V \approx	581 - 730 V \approx / 653 - 822 V \approx 726 - 913 V \approx
Nominal/maximum charging/discharging current			100 A \approx
Max. C-rate	with STPS X 30 with STPS X 50	1C --	0,7C/0,6C/0,5C --/--/1C 0,5C/0,4C/0,4C 0,8C/0,7C/0,6C
Overvoltage category			III
Cell		Lithium NMC prismatic (Samsung SDI)	
Cell balancing		DynamiX Battery Optimizer	
Cycles expected @ 100% DoD 70% SoH 23°C +/-5°C 1C/1C		6,000	
Cycles expected @ 100% DoD 70% SoH 23°C +/-5°C 0.5C/0.5C		8,000	
Efficiency (battery)		up to 98%	
Self-consumption (standby)		5 W (without battery inverter)	
Operating temperature		0°C to 50°C (derating at low temperatures)	
Ambient temperature		0°C to 50°C (optimal: 25°C +/-5°C)	
Ambient temperature for capacity guarantee		10°C to 45°C	
Humidity		0 to 80% (non-condensing)	
Cooling concept		Passive via fins and active via fans	
Altitude of installation site		< 2,000 m above sea level	
Max. noise emission (per fan running)		65 dB	
Weight	Total	346 kg	426 kg 482 kg 538 kg
	Battery module APU Cabinet	56 kg 13 kg 107 kg	56 kg 13 kg 130 kg
Dimensions of cabinet (H x W x D)		1208 mm x 608 mm x 808 mm	1608 mm x 608 mm x 808 mm
with wall bracket		1208 mm x 608 mm x 990 mm	1608 mm x 608 mm x 990 mm
Tilt height of cabinet forwards, backwards/sideways		1426 mm/1339 mm	1778 mm/1705 mm
2155 mm/2090 mm			
Certificates/standards	Cell	IEC 62619:2017, UL 1642, UN 38.3	
	Battery module	UN 38.3, IEC 62619:2017, IEC 62620:2014	
	Product	CE, UN 38.3, IEC 62619:2017, IEC 61010-1+A1:2016, IEC 61508:2010, IEC 61000-6-2:2016, IEC 61000-6-4:2019, IEC 61000-6-7:2015, 2006/66/EG (Battery Directive)	
Guarantee		10-year performance guarantee, 10-year system guarantee	
Recycling		TESVOLT offers a free take-back scheme for batteries from Germany	
Protection class		IP 20	
Degree of protection		I	
Pollution degree		PD 2	
IK class		IK 10	
Battery specification as per IEC 62620:2014		INP46/175/127/[1P22S]M/-20+60/90	

TECHNICAL DATA FOR BATTERY INVERTER (SMA STPS X 30/50)

Type designation	STPS X 30	STPS X 50
Nominal power	30 kVA	50 kVA
AC voltage range		340 V to 477 V
Grid frequency range		44 Hz to 66 Hz
DC voltage range		200 V \approx to 980 V \approx
Dimensions (H x W x D)		837.3 mm x 772 mm x 443.8 mm
Max. efficiency/European efficiency	98%/97.6%	98%/97.2%
Self-consumption (standby)		25 W
Operating temperature		-25 to 60°C (with derating)
Noise emission (typical)		69 dB (A)
Weight		104 kg
Protection class		IP 65 NEMA 4X
Communication		Modbus (SMA, Sunspec), SMA Speedwire, Webconnect
Topology/cooling principle		Three-phase/active
Guarantee		5 years standard SMA guarantee (optional: 10 years)
Certificates		see SMA website for more: https://www.sma.de

SYSTEM CONFIGURATIONS

The tables show a selection of possibilities for the different product variants depending on the battery energy and number of SMA STPS X 30/50 battery inverters (other possibilities on request).

TS HV 30 E

Number of TS HV 30 E	Energy System								
40	1280 kWh								
20	640 kWh								
16	512 kWh								
12	384 kWh								
10	320 kWh								
8	256 kWh								
6	192 kWh								
5	160 kWh								
4	128 kWh								
3	96 kWh								
2	64 kWh								
1	32 kWh								
Output		30 kW	60 kW	90 kW	120 kW	150 kW	180 kW	240 kW	300 kW
Number of SMA STPS X 30		1	2	3	4	5	6	8	10

TS HV 50 E

Number of TS HV 50 E	Energy System										
	TS HV 50/5-20	TS HV 50/6-20	TS HV 50/7-20								
40	1600 kWh	1920 kWh	2240 kWh								
20	800 kWh	960 kWh	1120 kWh								
16	640 kWh	768 kWh	896 kWh								
12	480 kWh	576 kWh	672 kWh								
10	400 kWh	480 kWh	560 kWh								
8	320 kWh	384 kWh	448 kWh								
6	240 kWh	288 kWh	336 kWh								
5	200 kWh	240 kWh	280 kWh								
4	160 kWh	192 kWh	224 kWh								
3	120 kWh	144 kWh	168 kWh								
2	80 kWh	96 kWh	112 kWh								
1	40 kWh	48 kWh	56 kWh								
Output				30 kW/50 kW	60 kW/100 kW	90 kW/150 kW	120 kW/200 kW	150 kW/250 kW	180 kW/300 kW	240 kW/400 kW	300 kW/500 kW
Number of SMA STPS X 30/50				1	2	3	4	5	6	8	10

TS HV 80 E

Number of TS HV 80 E	Energy System										
	TS HV 50/8-20	TS HV 50/9-20	TS HV 50/10-20								
40	2560 kWh	2880 kWh	3200 kWh								
20	1280 kWh	1440 kWh	1600 kWh								
16	1024 kWh	1152 kWh	1280 kWh								
12	768 kWh	864 kWh	960 kWh								
10	640 kWh	720 kWh	800 kWh								
8	512 kWh	576 kWh	640 kWh								
6	384 kWh	432 kWh	480 kWh								
5	320 kWh	360 kWh	400 kWh								
4	256 kWh	288 kWh	320 kWh								
3	192 kWh	216 kWh	240 kWh								
2	128 kWh	144 kWh	160 kWh								
1	64 kWh	72 kWh	80 kWh								
Output				30 kW/50 kW	60 kW/100 kW	90 kW/150 kW	120 kW/200 kW	150 kW/250 kW	180 kW/300 kW	240 kW/400 kW	300 kW/500 kW
Number of SMA STPS X 30/50				1	2	3	4	5	6	8	10

TESVOLT AG

Am Heideberg 31 | 06886 Lutherstadt Wittenberg
 Deutschland | Germany
 Phone +49 (0) 3491 8797 100
 info@tesvolt.com | www.tesvolt.com



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 101017877

This data sheet is strictly informational and is not legally binding. The exact specifications and/or product features (particularly in case of further development of the product) may differ somewhat from the information provided here. Subject to errors and changes. Please read the safety and installation instructions carefully and completely before using the product. In case of purchase, the currently valid guarantee policies and the general terms and conditions of delivery and business of TESVOLT AG apply.

Registration in the manufacturer's myTESWORLD portal (<https://mytesworld.tesvolt.com>) is required to use the energy management system (EMS) TESVOLT Energy Manager.
 Registration in Sunny Portal powered by ennexOS from the manufacturer SMA ([Sunny Portal powered by ennexOS](https://www.sunnyportal.com)) is required to use the energy management system (EMS) Data Manager M.