

XG3-10KTL

Single Phase On-Grid Solar Inverter



Efficient Higher Revenue

- 2 MPP Trackers , Max. input current per string: 20A
- 150% DC Input Oversizing
- Compatible with high power modules



Intelligent Simple O&M

- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- Intelligent Fault Detection: AC side voltage and current waveforms real-time recorded, fast fault location
- Support RS485/WiFi/4G: remote monitoring and operation via PC or mobile phones



Reliable Worry Free

- IP66 Protection Degree: support outdoor installation
- AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

	XG3KTL-2M	XG3.68KTL	XG4KTL	XG4.2KTL	XG4.6KTL	XG5KTL	XG6KTL	XG7KTL	XG8KTL	XG10KTL	XG7KTL1	XG8KTL1	XG10KTL1
Input (DC)													
Max. Input Power	4.5kW	5.52kW	6kW	6.3kW	6.9kW	7.5kW	9kW	10.5kW	12kW	15kW	10.5kW	12kW	15kW
Max. Input Voltage							600V						
Start Voltage							80V						
Rated Input Voltage							360V						
MPPT Voltage Range							50V ~ 550V						
Number of MPP Trackers							2						
Number of String per MPPT						1 / 1					1 / 2		
Max. Current per MPPT						20A					14A / 28A		
Max Short Circuit Current per MPPT						26A					18.2A / 36.4A		
Output (AC)													
Max. Output Current	15A	16A	20A	21A	23A ^d	25A ^d	30A	35A	40A	45.5A	35A	40A	45.5A
Rated Output Power	3kW	3.68kW	4kW	4.2kW	4.6kW	5kW ^a	6kW	7kW	8kW	10kW	7kW	8kW	10kW
Max. Output Power	3.3kVA	3.68kVA	4.4kVA	4.62kVA	5kVA ^b	5.5kVA ^c	6.6kVA	7.7kVA	8.8kVA	10kVA	7.7kVA	8.8kVA	10kVA
Rated Grid Frequency							50Hz / 60Hz						
Rated Grid Voltage							220Vac / 230Vac / 240Vac						
Power Factor							>0.99 (0.8 leading ~ 0.8 lagging)						
THDi							<3% (Rated Power)						
Efficiency													
Max. Efficiency	98.10%				98.30%						98.10%		
European Efficiency	97.30%				97.40%						97.30%		
MPPT Efficiency							99.90%						
Protection													
DC switch							Optional						
DC Reverse Polarity Protection							Yes						
Anti-islanding Protection							Yes						
AC short Circuit Protection							Yes						
Residual Current Monitoring Unit							Yes						
Insulation Resistance Monitoring							Yes						
Ground Fault Monitoring							Yes						
Grid Monitoring							Yes						
PV String Monitoring							Yes						
Surge Protection							Yes						
AFCI Protection							Optional						
Communication													
Display							LCD / LED+APP						
Communication							RS485 / WiFi / 4G						
Standard Compliance													
Certification					IEC/EN 62109-1/2, IEC/EN 61000-6-1/3, EN50549, IEC61727/IEC62116, CEI0-21, C10/C11, G98/G99, RD244, UNE217001, UNE217002, TOR Erzeuger, AS4777, ABNT, NB/T 32004								
General Data													
Dimensions (W x H x D)					380 x 380 x 160 mm								
Weight					13kg								
Operating Temperature Range					-30° C ~ +60° C								
Cooling Method					Natural						Smart Cooling		
Protection Degree					IP66								
Max. Operating Altitude					4000m								
Relative Humidity					0 ~ 100%								
Topology					Transformerless								
Night Power Consumption					<1W								

- a: For AS4777, Rated Output Power of XG5KTL is 4999W .
- b: For VDE-AR-N 4105 , Max . Output Power of XG4K6TL is 4600VA . For AS4777, Max . Output Power of XG4K6TL is 4999VA .
- c: For AS4777, Max. Output Power of XG5KTL is 4999VA .
- d: For AS4777, Max . Output Current of XG4K6TL and XG5KTL is 21.7A .



Sales E-mail: solar@invt.com.cn Service E-mail: solar-service@invt.com.cn Website: www.invt-solar.com