



Building the Solar World with
Technology & Wisdom

Sun-Pursuit Pro Series

TOPCon Bifacial
132 - cell Module

TW-625HDB-1 FULL BLACK

600-625W

0-3% Positive Tolerance



Monocrystalline



Half Cell



16BB



Grade A



• MODULE FEATURES



High efficiency

TOPCon technology improves efficiency, increases power generation, and contributes to lower LCOE.



Lower heat spot risk

Innovative circuit design and "Half Cell" structure decrease the temperature of heat spots and effectively reduce power loss.



Excellent low-light performance

Reliable performance in low-light conditions such as in the morning, at dusk or during raining days.



Resilient to extreme weather

Carefully selected materials ensure the module still works well under the condition of 2400Pa wind load and 5400Pa snow load.



PID resistant

High quality solar cell and advanced processing technology contribute to excellent PID resistance performance.



Double-sided electricity generation

Power can be generated on both sides to support additional output gains of up to 25%. The multi-busbar half-cut technology can boost energy density to deliver higher output.


• Quality Certification



• Product Qualification



• Performance Warranty



15 Years Product Warranty

30 Years Linear Power Warranty



Building the Solar World with
Technology & Wisdom

TW-625HDB-1

• Product Specification •

Cell Type	Mono crystalline
Cell Quantity	132 cell
Cell Size (mm)	182*105
Module Size (mm)	2382*1134*30
Module Weight (kg)	33.5
Glass Thickness (mm)	2.0
Frame Material	Anodized aluminum alloy
Junction Box	IP68
Cable/Connector	4mm ² , MC4 compatible
Cable Length	+300mm/-300mm; or Customize
Max System Volt (V)	1500V DC
Max Fuse Rate (A)	30
Power Tolerance (%)	0→3%

• Electrical Characteristics •

STC standard performance >>>

Power Level	600	605	610	615	620	625
Pmax(W)	600	605	610	615	620	625
Vmp(V)	40.30	40.50	40.70	40.90	41.10	41.30
Imp(A)	14.90	14.95	15.00	15.05	15.10	15.15
Voc(V)	48.51	48.71	48.91	49.11	49.31	49.51
Isc(A)	15.76	15.81	15.86	15.93	15.98	16.03
Module Efficiency (%)	22.21	22.40	22.58	22.77	22.95	23.14

NOCT standard performance >>>

Power Level	600	605	610	615	620	625
Pmax(W)	450	454	458	461	465	469
Vmp(V)	37.76	37.95	38.14	38.33	38.51	38.70
Imp(A)	11.92	11.96	12.00	12.04	12.08	12.12
Voc(V)	46.10	46.29	46.48	46.67	46.86	47.05
Isc(A)	12.62	12.66	12.71	12.75	12.79	12.83

• Bifacial Output-backside Power Gain •

5%Pmax(W)	630	635	641	646	651	656
5% Module Efficiency	23.30	23.50	23.70	23.90	24.10	24.30
15% Pmax(W)	690	696	702	707	713	719
15% Module Efficiency	25.52	25.80	26.00	26.20	26.40	26.60
25% Pmax(W)	750	756	763	769	775	781
25% Module Efficiency	27.74	28.00	28.20	28.50	28.70	28.92


• Temperature Characteristics •

Operating Temp(°C)	-40~85
Operating Humidity(°C)	5~85
Hail Load Tolerance	25mm hailstone with velocity of 23m/s
Temp Coefficient	-0.340
Temp Coefficient Isc (%/°C)	0.04
Temp Coefficient Voc (%/°C)	-0.25
Operating Temp (°C)	44±2





Add: Shangman Industrial Park, Caobu Town
Rudong County, Nantong City, Jiangsu Province, China
Tel: 86-513-81900128
Web: www.techwisesolar.com
Email: salesdept@techwisesolar.com

• Engineering Drawings •



• I-V Curve •



• Packaging Info •

Pieces per Pallet	36
Size of Packaging (mm)	2396*1125*1270
Weight of per Pallet (kg)	1231
Pieces per Container	720
Size of Container	40'HC

All data and specifications included in this brochure may be subject to be modified without notice. All Rights reserved by TechWise Solar Co. (Mar 2024 V3 Edition)