



# Motorcycle Battery



Maintenance Free motorcycle battery, using AGM separator and Lead-Calcium alloy plate, has ultra-low self-discharge rate, shock resistance and excellent low-temperature starting performance.

Model	Voltage (V)	Capacity (10HR/Ah)	CCA	Dimension (mm)			Weight (Kg)	Plate Per Cell
				Length	Width	Height		
12N2.5	12	2.5	60	80	77	105	1.10	3
YT4	12	2.6	95	113	70	89	1.21	5
	12	3.4	110	113	70	89	1.28	6
	12	3.8	125	113	70	89	1.38	7
	12	4.1	135	113	70	89	1.45	7
YT5	12	5.0	130	113	70	109	1.73	6
	12	5.5	145	113	70	109	1.81	7
12N5	12	4.8	115	120	61	125	1.79	6
	12	5.5	130	120	61	125	1.92	7
12N6.5	12	5.5	125	139	66	102	1.90	7
	12	6.5	150	139	66	102	2.01	8
YT7	12	5.8	145	151	87	94	2.26	9
	12	7.2	160	151	87	94	2.42	9
	12	7.9	180	151	87	94	2.52	9
YT7L	12	7.0	145	114	69	131	2.18	7
	12	7.0	150	114	69	131	2.30	7
12N7A	12	6.3	125	136	76	126	2.34	7
	12	7.0	140	136	76	126	2.58	8
12N7B	12	6.8	145	146	59	127	2.24	8
	12	7.0	150	146	59	127	2.37	9
YT9	12	7.9	180	151	87	106	2.70	9
	12	9.0	195	151	87	106	2.80	9
12N9	12	6.5	110	136	76	133	2.66	7
	12	7.2	130	136	76	133	2.75	7
	12	8.5	155	136	76	133	2.82	7
YT12	12	10.0	200	151	87	132	3.35	8
	12	12.0	215	151	87	132	3.50	9
YT14A	12	11.0	190	151	87	149	3.60	8
	12	14.0	220	151	87	149	4.20	9
YT14B	12	14.0	200	132	89	163	3.95	9
YT20	12	15.0	250	171	87	163	4.80	9
	12	18.0	280	171	87	163	5.10	10