


# Everest G12R Series 435-460W

**96-cell** Bifacial HJT Half Cell  
Double-glass Solar Module



### HJT Technology

Combining gettering process and  $\mu\text{-Si}$  technology to ensure higher cell efficiency and higher module power



### Up to 95% Bifaciality

Natural symmetrical bifacial structure bringing more energy yield from the backside.



### Sealing with PIB

Integrated coating frames ensuring modules passing the IEC salt-mist test level 8



### Ideal choice for rooftop system

Suitable for various rooftop projects




## WARRANTY

Product  
Warranty **15**  
years

Linear  
Power  
Warranty **30**  
years

### Complete System and Product Certifications:

- IEC61215, IEC61730
- ISO9001:2015 Quality Management System
- ISO14001:2015 Environment Management System
- ISO45001:2018 Occupational Health and Safety
- IEC62941:2019 Terrestrial photovoltaic (PV) modules- Quality system for PV module manufacturing




- \* First year power degradation  $\leq 1\%$
- \* Annual power degradation (2-30 year)  $\leq 0.3\%$
- \* Power output until the 30th year  $\geq 90.3\%$

- BloombergNEF Tier 1 PV module manufacturer
- Reinsurance underwritten by Ariel Re

## Engineering Drawings

Unit: mm



## Mechanical Characteristics

Cell Type	HJT
No. of Cells	96 (6x16)
Dimensions	1762x1134x30mm
Weight	21.8 kg
Junction Box	IP68
Cable	4mm <sup>2</sup> ; 1250mm or customized; UV resistant
Connector	MC4 / MC4-Evo2A / PV-H4 / Z4S-abcd / ST4
Frame	Anodized aluminum alloy frame
Max Static Load (front side/rear side)	5400Pa / 2400Pa
Glass	Dual glass, 1.6mm

## Electrical Characteristics

### STC

HS-210R-B96	DS435	DS440	DS445	DS450	DS455	DS460
Maximum Power (Pmax/W)	435	440	445	450	455	460
Module Efficiency (%)	21.8	22.0	22.3	22.5	22.8	23.0
Voltage at Pmax (Vmp/V)	30.50	30.61	30.72	30.83	30.94	31.05
Current at Pmax (Imp/A)	14.27	14.38	14.49	14.60	14.71	14.82
Open Circuit Voltage (Voc/V)	36.42	36.52	36.62	36.72	36.82	36.92
Short Circuit Current (Isc/A)	15.20	15.31	15.42	15.53	15.64	15.75

STC: AM1.5, 1000W/m<sup>2</sup>, 25°C.


### BSTC

Maximum Power (Pmax/W)	487	493	499	504	510	515
Voltage at Pmax (Vmp/V)	30.61	30.72	30.83	30.94	31.05	31.16
Current at Pmax (Imp/A)	15.94	16.07	16.19	16.31	16.44	16.56
Open Circuit Voltage (Voc/V)	36.55	36.65	36.75	36.85	36.95	37.05
Short Circuit Current (Isc/A)	17.05	17.17	17.29	17.42	17.54	17.66

BSTC: AM1.5, 1000W/m<sup>2</sup>, 135W/m<sup>2</sup>, 25°C.

## I-V Curve

(HS-210R-B96DS445)



## Temperature Characteristics

Temperature Coefficient of Pmax	-0.24%/°C
Temperature Coefficient of Voc	-0.22%/°C
Temperature Coefficient of Isc	+0.04%/°C

## Operating Conditions

Nominal Operating Cell Temp.	44±2°C
Operating Temperature	-40~+85°C
Maximum System Voltage	DC1500V (IEC)
Maximum Series Fuse Rating	30A
Tolerance of Pmax	0~+3%
Power Selection	0~+5W
Bifaciality	90±5%
Safety Class	Class II

## NOCT

Maximum Power (Pmax/W)	332	335	339	343	347	351
Voltage at Pmax (Vmp/V)	29.12	29.23	29.34	29.45	29.55	29.65
Current at Pmax (Imp/A)	11.40	11.49	11.58	11.67	11.76	11.84
Open Circuit Voltage (Voc/V)	34.76	34.86	34.95	35.05	35.14	35.24
Short Circuit Current (Isc/A)	12.15	12.24	12.32	12.41	12.50	12.59

NOCT: AM1.5, 800W/m<sup>2</sup>, 20°C, 1m/s.

## Packaging

	40HQ
Modules Per Pallet	36
Pallets Per Container	26
Modules Per Container	936



ANHUI HUASUN ENERGY CO., LTD. All rights reserved © 2020-2024

NO.99 Qingliu Road, Economic and Technological Development Zone, Xuancheng, Anhui, China  
 Tel: 0086-563-3318095 www.huasunsolar.com  
 sales@huasunsolar.com customerservice@huasunsolar.com

The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Anhui Huasun reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the latest version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.