

More Usable Energy 90% depth of discharge



High EnergySingle cell with 200Ah



High Expansibility

Max 63 batteries in parallel.Scalable from 10.24kWh to 645.12kWh



Flexible Installation

Wall mounted or floor stand



Safe&Reliable

Lithium iron phosphate cell Cobalt free



Perfect Compatibility

Compatible with mainstream inverter brand



| Model | LVTS-512200-G2 |
|-------|----------------|
| | |

| Performance | | |
|---------------------------|-----------------|--|
| Nominal Voltage | 51.2 Vdc | |
| Nominal Capacity | 200Ah | |
| Battery Energy | 10.24 kWh | |
| Charge Voltage | 55.68-56.16 Vdc | |
| Discharge Voltage | 45.6-56.16 Vdc | |
| Maximum Charge Current | 120A | |
| Maximum Discharge Current | 170A | |
| Maximum Charge Power | 6144W | |
| Maximum Discharge Power | 8704W | |
| Short circuit current | 540A | |

| Communication | |
|---------------|-----------------------------|
| Display | LED indicator + LCD Display |
| Communication | RS232、RS485、CAN |

| General Specification | |
|------------------------------|---|
| Dimension(W×D×H mm) | 465×186×695mm |
| Weight (Kg) | 83.5kg |
| Installation | Floor Stand |
| Working Temperature | -20°C~60°C |
| Storage Temperature | ≤25 °C,12 months; ≤35 °C,6 months; ≤45°C,3 months |
| Operating / Storage Humidity | ≤ 95%RH |
| Max Operating Altitude | ≤2000m |
| IP Rating | IP20 |
| Cell Technology | LiFePO₄, Lithium lron Phosphate |
| Cycle life | 6000 Cycles @ 90% DOD/25°C/0.5C,60% EOL |
| Warranty | 5 years |
| Scalability | Max 63 batteries in parallel |

| Ordering and Deliverable Part | |
|-------------------------------|---|
| Product ordering part | LVTS-512200 battery (cable/wall mount included) |