



ENERGY
STORAGE



BYHV-1000SAC

VoyagerPower 2.0 Air Cooling Energy Storage System

ZHEJIANG BENYI NEW ENERGY CO.,LTD.

CHANGJIANG RD, WENZHOU DAQIAO INDUSTRY PARK, BEIBAIXIANG TOWN, YUEQING, WENZHOU CITY, ZHEJIANG PROVINCE, CHINA

TEL: +86-577-5717 7008 FAX: +86-577-5717 7007

✉ info@benyi.com

🌐 www.benyi.com

♻️ This catalogue has been printed on ecological paper.

© Zhejiang Benyi New Energy Co., Ltd. All rights reserved.

⚠️ If the models and specifications in this product catalogue change due to product updates, we will not provide prior notification.



VERSION: 20240814-01

Product Introduction

VoyagerPower 2.0 is a container energy storage system introduced by Beny, covering BESS from 1MWh~5MWh. ESS adopts an "All-In-One" design concept, with ultra-high integration that combines energy storage batteries, BMS (Battery Management System), PCS (Power Conversion System), EMS(energy management system), fire protection, air conditioning, and more into a single unit, making it adaptable to various scenarios. This product features a prefabricated cabin design flexible deployment, convenient transportation, and no need for internal wiring and debugging. It responds quickly, boasts high reliability, and offers functions such as peak shaving, power capacity expansion, emergency backup power, grid balancing, capacity management, and multi-level parallel connection.

Application Scenario

grid side: load corresponding , peak regulation, grid dispatching, energy transfer;
user side: peak cutting and valley filling , anti-reflux zero feedback, time-of-sale price, optical storage and charging;
micro-grid: light storage and firewood micro-grid , automatic and off-grid switching, black starting;

Product Features

Safe and reliable

IP55 protection grade design, cluster level aerosol layout, BMS and AC/DC multi-layer protection Settings to ensure the safe operation of the system;

Cost optimization

Small size, light weight, save floor space and installation costs, can be pre-installed whole system transportation, long life, low failure rate, low operation and maintenance costs;


Efficient and convenient

Batteries, PCS, etc., all adopt modular design for easy installation and transportation, and can remotely guide configuration, equipment management, data analysis, fault prediction, etc.

Rich scene

Application strategies can be customized in different environments to meet product requirements;

Specifications and Model Description



Tip: "/" can be sequentially stacked after

Product Parameter



Type designation	BYHV-1000SAC	BYHV-1000SAC-1H
Battery Data		
Cell type	LFP 3.2V / 280Ah	
Battery configuration	(1P16*15)*5	
Battery capacity	1075.5kWh	
Battery current	655A	1310A
Battery voltage range	624V-876V	
AC Output (On-grid)		
Nominal AC power	500kW	1MW
Nominal AC voltage	400Vac 3P4W+PE/3P3W-PE	
Max. output current	794A	1588A
THDi	<3% (at rated power)	
Grid frequency range	50Hz/60Hz (settable)	
AC voltage range	-15%~10% (settable)	
Power factor	>0.99 (at rated power)	
AC Output (Off-grid)		
Rated AC output voltage	400Vac	
Voltage accuracy	1%	
Max. output current	794A	1588A
THDi	<3% (linear load)	
Rated output frequency	50Hz /60Hz	
Overload capability	110% overload	
System parameter		
Isolation method	Isolation Transformer(option)	
Automatic and off-grid	Support(option)	
Dimension (W*H*D)	6058*2591*2438	
Weight	16000Kg	16200Kg
IP grade	IP55	
Anti-corrosion degree	C3[Support C5]	
Operating temperature	-30 to 55°C(>45°C derating)	
Operating humidity	0 ~ 95%(non-condensing)	
Working altitude	3000m	
Temperature control	Intelligent air cooling	
Fire suppression system	NFPA 69 explosion prevention and Aerosol	
communication protocol	Modbus TCP, MQTT	
Standard	IEC 62477, IEC 61000-6-2, IEC 61000-6-4, IEC 62619, EN 50549-1, NC RfG, EN 50549, VDE-AR-N4110, UN 38.3/UN 3536	