

Aluminium alloy core



Strict Quality Control

Red Cable

Certification

Specification

Conductor

Insulation

Sheath

Color

High and Low

Temperature Resistance



**MULTICOLOUR AVAILABLE** 

Black Cable

YOU CAN CHOOSE FROM TWO COLORS





Flame

Retardant

Multiple

Protection





1.5mm<sup>2</sup>,2.5mm<sup>2</sup>,4.0mm<sup>2</sup>,6.0mm<sup>2</sup>,10.0mm<sup>2</sup>,16.0mm<sup>2</sup>

## Number of Cores Single Core Aluminum alloy

XLPO

XLPO


25.0mm<sup>2</sup>,35.0mm<sup>2</sup>

TÜV, CE

Black ,Red or Customized

Transport Package Drum or Roll Rated voltage AC U0/U 1.0/1.0 KV, DC 1.5 KV Voltage test on completed cable AC6.5KV/5min, DC15KV/5min **CROSS-LINKED POLYOLEFIN** Materials for photovoltaics Double-layer sheath, irradiation process, with UV resistance, flame retardant properties





Copper-aluminium connectors for photovoltaics

Copper-aluminium

conversion connectors

MC4

Aluminium 6mm<sup>2</sup> vs Tinned Copper 4mm<sup>2</sup>

Tinned copper cable

Black wire: pv aluminium alloy

Pin: Copper and Aluminium Conversion

wire 1\*6mm<sup>2</sup>

Inserts(-)


Inserts (+)

Wooden pallet packing

Schematic diagram of loading cabinet

Member of the Association for Science, Technology and Innovation (ASTI)

Compliance and cost reduction



copper (+)

copper (-)

**Boutique Customisation** 

Wooden pallets + pallets

Certificate - Cepnydowan - 40発達 - Certificat

(€

High-tech enterprises

**REDUCE COSTS** 

Photovoltaic Aluminum

Alloy Cable











挂牌企业 灵单位 浙江品恩泰克科技有限公司 往牌代码: 783656

**Equity listed companies** 

字波収収交易中心

4 宁波市科技创新协会