

Residential ESS Solution

Spring | Rack-Mounted Battery(LV)



SE-G 5.1



SE-G 10.2

- Energy Capacity**
5.12kWh
51.2V
100Ah
- Installation**
Rack-mounted
Wall-mounted
Stack-mounted
Indoor
- Size and weight**
440×540×133
(mm) (W×D×H)
45 kg
- Maximum Output Power**
2.5kW
- Operating Conditions**
Charge:0~55°C
Discharge:-20~55°C
- Warranty**
5 Years

Support 3.6/5/6/8kW single-phase or three-phase inverters, meeting the application requirements of 2-4 hours

Reliable
Support 0.5C charge and discharge,
Wide temp range:-20°C to 55°C

Smart
Built-in circuit breaker
Intelligent BMS

Convenient
Auto networking, No DIP Switches, easy maintaince,
support remotely monitoring and upgrade the firmware

Flexible
Easy to expand, Max. 64 units in parallel(327kWh/655kWh)
Suited to residential and commercial

- Energy Capacity**
10.24kWh
51.2V
200Ah
- Installation**
Rack-mounted
Wall-mounted
Stack-mounted
Indoor
- Size and weight**
710×540×133
(mm) (W×D×H)
85 kg
- Maximum Output Power**
5kW
- Operating Conditions**
Charge:0~55°C
Discharge:-20~55°C
- Warranty**
5 Years

Support 8-20kW single-phase or three-phase inverters, meeting the application requirements of 2-4 hours