

415W-435W


CMD-108BDS

22.31%

MAXIMUM EFFICIENCY

108

HALF CELLS



- ◆ Exceeds PV durability standards as per **DIN ISO 12543-4**
- ◆ Highly resistant to impact according to **DIN EN 12600**
- ◆ Highly durable under mechanical loads as per **DIN EN 18008-1 & 2**
- ◆ Module overhead safety ensured by extended adhesion test as per **DIN EN ISO 8510-2**
- ◆ Fire resistant according to **DIN 4102-1**
- ◆ **DIBt** certified (from the German Institute for Construction Technology) for safety, durability, and compliance in building-integrated applications

Ver. 25.5.1


30 YEARS

Performance Warranty

up to **30 YEARS***
Product Warranty

*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. For extensions, please contact AESOLAR staff.

OUR PERFORMANCE WARRANTY



AESOLAR

Since 2003



LID
RESISTANT



PID
RESISTANT



SALT CORROSION
RESISTANT



SAND
RESISTANT



AMMONIA
RESISTANT




HIGHLY STABLE
AND TOUGH



AE CMD-108BDS 415W-435W

SOLAR PANELS DESIGNED FOR CARPORTS

BIFACIAL • DOUBLE-GLASS



Units: mm



Electrical specifications (STC*):

Nominal max. power	P_{max} (Wp)	415	420	425	430	435
Maximum operating voltage	V_{MPP} (V)	31.81	32.04	32.25	32.43	32.64
Maximum operating current	I_{MPP} (A)	13.05	13.11	13.18	13.26	13.33
Open-circuit voltage	V_{oc} (V)	37.67	37.86	38.08	38.26	38.46
Short-circuit current	I_{sc} (A)	13.95	14.03	14.10	14.17	14.23
Module efficiency	η (%)	21.28	21.54	21.80	22.05	22.31
Power tolerance	(W)			0~+5		
Maximum system voltage	(V)			1500		
Maximum series fuse rating	(A)			25		

*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance P_{max} : $\pm 3\%$

Electrical specifications (NMOT*):

Nominal max. power	P_{max} (Wp)	315	320	325	330	335
Maximum operating voltage	V_{MPP} (V)	29.80	30.13	30.44	30.72	31.03
Maximum operating current	I_{MPP} (A)	10.57	10.62	10.68	10.74	10.80
Open-circuit voltage	V_{oc} (V)	34.85	35.20	35.57	35.94	36.33
Short-circuit current	I_{sc} (A)	11.30	11.36	11.42	11.48	11.53

*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

Bifacial electrical specifications

Max. power front-side	P_{max} front (Wp)	415	420	425	430	435
Backside Power Gain		5% 10%	5% 10%	5% 10%	5% 10%	5% 10%
Total equivalent power	$P_{max equ}$ (Wp)	436 457	441 462	446 468	452 473	457 479
Module efficiency	η (%)	22.35 23.42	22.62 23.70	22.89 23.98	23.16 24.26	23.43 24.54

*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

Mechanical and design specification

Cell type	n-Type TOPCon technology, half-cut cells
No. of cells	108
Bifaciality	80 $\pm$ 5%
Front cover	2.0 mm glass, high transmission, AR coated, tempered
Encapsulation	POE
Back cover	2.0 mm, high transmission solar glass, tempered
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable (Including Connector)	1 x 4 mm², 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	1721 mm x 1133 mm x 30 mm
Weight	23.5 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m²
Snow load	5400 Pa or 550 kg/m²
Fire rating	Class A (according to UL 790)
Transparency	8%


Packaging information

L: 1755 mm	H: 1245 mm	W: 1140 mm	36 pcs	880	936 pcs
			One pallet		40HQ

Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of P_{max}	-0.29 %/°C
Temp. coefficient of V_{oc}	-0.25 %/°C
Temp. coefficient of I_{sc}	0.046 %/°C
Nom. operating cell temp. NOCT	42 $\pm$ 2°C

SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730
Regular Production Surveillance
www.tuv.com

IEC 62716 (Ammonia corrosion)
IEC 61701 (Salt mist corrosion)
IEC 60068 (Sand and dust)
IEC 62804 (PID resistance)



The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.



Since 2003

+49 8231 978268 0
sales@ae-solar.com
www.ae-solar.com

AESOLAR
Senefelderstraße 23
86368 Gersthofen, Germany