

Stalker Plus 395-415Wp

High performance solar module
108 halfcell, monocrystalline


The advantages:

- 25** Years 25 years manufacturer's warranty
- HC** Highest module performance through Half-Cut-technology and tested materials
- Wp** Guaranteed positive power tolerance from 0-5 Wp by individual measurement
- 2.400 Pa** Maximum 2400 Pa snow load
- 100%** 100% electroluminescence inspection
- IP 68** High quality junction box and connector systems



Exclusive linear high performance guarantee!



• 25 years manufacturer's guarantee on 85% of the nominal performance



Electrical data (at standard conditions (STC) irradiance 1000 watt/m², spectrum AM 1,5 at a cell temperature of 25°C)

Type	Nominal output Pmpp	Nominal voltage Umpp	Nominal current Impp	Short circuit current Isc	Open circuit voltage Uoc	Module conversion efficiency
NB-395-54M	395 Wp	30,32V	13,03A	13,71A	36,90V	20,23%
NB-400-54M	400 Wp	30,42V	13,15A	13,78A	36,98V	20,48%
NB-405-54M	405 Wp	30,52V	13,27A	13,85A	37,06V	20,74%
NB-410-54M	410 Wp	30,62V	13,39A	13,92A	37,14V	21,00%
NB-415-54M	415 Wp	30,79V	13,48A	14,01A	37,31V	21,25%

I-V Curve



Design

Frontside	3,2 mm hardened, low-reflection white glass
Cells	108 monocrystalline high efficiency cells
Backside	Composite film
Frame	35 mm silver aluminium frame

Mechanical data

L x W x H	1722 x 1134 x 30 mm
Weight	22,0kg with frame

Power connection

Socket	Protection Class IP68
Wire	approx. 1,2 m, 4 mm ²
Plug-in system	Plug/socket IP68, Stäubli EVO2 / EVO2 pluggable

Limit values

System voltage	1500V~2000V DC
NOCT (nominal operating cell temperature)*	45°C +/-2K
Max. load-carrying capacity	2400 N/m ²
Reverse current feed IR	20,0 A
Permissible operating temperature	-40°C to 85°C / -40F to 185F

(No external voltages greater than Uoc may be applied to the module)

* NOCT, irradiance 800 W/m²; AM 1,5; wind speed 1 m/s; Temperature 20°C

Temperature coefficients


Voltage Uoc	-0,27 %/K
Current Isc	0,048 %/K
Output Pmpp	-0,35 %/K

Low-light performance

I-U characteristic curve	Current Ipp	Voltage Upp
200 W/m ²	2,24 A	40,05 V
400 W/m ²	4,51 A	40,51 V
600 W/m ²	6,74 A	40,82 V
800 W/m ²	8,91 A	41,17 V
1000 W/m ²	10,94 A	41,61 V

Packaging

Module pieces per pallet	36
Module pieces per HC-container	936



All dimensions in mm