

EL325-345P-72H(5BB)

HALF CELL POLY CRYSTALLINE MODULE

East Lux
Power from East

KEY FEATURES



5 Busbar Solar Cell:

5 busbar solar cell adopts new technology to improve the efficiency of modules, offers a better aesthetic appearance, making it perfect for rooftop installation.



High Power Output:

With up to 345 Wp and 17.50 % efficiency, highest performing module of its kind on the market.



PID RESISTANT:

Limited power degradation caused by PID effect is guaranteed under strict testing condition (85 C /85%RH, 96hours) for mass production.



Low-light Performance:

Advanced glass and surface texturing allow for excellent performance in low-light environments.



Severe Weather Resilience:

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).



Durability against extreme environmental conditions:

High salt mist and ammonia resistance certified by TUV NORD.



Temperature Coefficient:

Improved temperature coefficient decreases power loss during high temperatures.

Reliable Quality


- Positive power tolerance: 0~+5W
- 100% EL double-inspection ensures modules are defects free
- Modules binned by current to improve system performance
- Potential Induced Degradation (PID) Resistant

Comprehensive Certificates

- IEC 61215, IEC 61730, UL1703, CEC Listed, MCS and CE
- ISO 9001:2008: Quality management systems
- ISO 14001:2004: Environmental management systems
- BS OHSAS 18001: 2007: Occupational health and safety management system
- Environmental policy: The first solar company in China to complete intertek's carbon footprint evaluation program and receive green leaf mark verification for our products

LINEAR PERFORMANCE WARRANTY

12 Years Product Warranty 25 Years Linear Power Warranty




Specifications subject to technical change and tests. East Lux reserves the right of final interpretation.


SPECIFICATIONS

Module Type	EL325P-72H		EL330P-72H		EL335PP-72H		EL340P-72H		EL345P-72H	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	325Wp	241Wp	330Wp	245Wp	335Wp	249Wp	340Wp	253Wp	345Wp	257Wp
Maximum Power Voltage (Vmp)	37.6V	35.0V	37.8V	35.3V	38.0V	35.6V	38.2V	35.9V	38.4V	36.2V
Maximum Power Current (Imp)	8.66A	6.89A	8.74A	6.94A	8.82A	6.99A	8.90A	7.05A	8.98A	7.10A
Open-circuit Voltage (Voc)	46.7V	43.3V	46.9V	43.6V	47.2V	43.8V	47.5V	44.0V	47.8V	44.2V
Short-circuit Current (Isc)	9.10A	7.40A	9.14A	7.45A	9.18A	7.52A	9.22A	7.98A	9.29A	8.05A
Module Efficiency STC (%)	16.49%		16.74%		17.00%		17.25%		17.50%	
Operating Temperature (°C)	-40C~+85C									
Maximum system voltage	1000VDC (IEC)									
Maximum series fuse rating	20A									
Power tolerance	0~+3%									
Temperature coefficients of Pmax	-0.38%/C									
Temperature coefficients of Voc	-0.31%/C									
Temperature coefficients of Isc	0.06%/C									
Nominal operating cell temperature (NOCT)	45±2C									

Engineering Drawings



Electrical Performance & Temperature Dependence



Mechanical Characteristics

Cell Type	Poly-crystalline 156×156mm (6 inch)
No. of Half-cells	144 (12×12)
Dimensions	1987×992×40mm (78.23×39.05×1.57 inch)
Weight	22.5 kg (49.6 lbs)
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67 Rated
Output Cables	anode 290mm, cathode 145mm or Customized Length

Packaging Configuration

26pcs/pallet, 52pcs/stack, 572 pcs/40'HQ Container

*STC: Irradiance 1000W/m²

Cell Temperature 25°C

AM=1.5

NOCT: Irradiance 800W/m²

Ambient Temperature 20°C

AM=1.5

Wind Speed 1m/s

* Power measurement tolerance: ± 3%