



**SLP350S-24 SLP355S-24 SLP360S-24 SLP365S-24**

**Electric Performance Parameters**

TYPE	SLP350S-24	SLP355S-24	SLP360S-24	SLP365S-24
Rated power (W)	350W	355W	360W	365W
Deviation of rated power (W)	0~+5W	0~+5W	0~+5W	0~+5W
Optimum operating voltage (Vmp)	38.13V	38.34V	38.56V	38.83V
Optimum operating current (Imp)	9.18A	9.26A	9.33A	9.40A
Open-circuit voltage (Voc)	46.48V	46.74V	47.00V	47.33V
Short-circuit current (Isc)	9.64A	9.72A	9.80A	9.87A
Temperature coefficient of open-circuit voltage	-0.36%/°C			
Temperature coefficient of short-circuit current	-0.07%/°C			
Temperature coefficient of rated power	-0.38%/°C			
Standard operating temperature	45±2°C			

STC: illumination intensity: 1000W/M<sup>2</sup>, battery temperature: 25°C, air quality=1.5  
 NOCT: illumination intensity: 800W/M<sup>2</sup>, environmental temperature: 20°C, air quality=1.5, wind speed: 1m/s

**Packaging Information**

Type of Cell	Monocrystalline silicon cell (156.75x156.75)
Cell Array	72(6x12)
Module Dimension	1960mm x 992mm x 40mm
Weight	22.1kg
Pallet Dimension	2005mm x1120mm x 1130mm(26 pieces/pallet)
Container loading information (40HQ)	572 pieces

**Operation Condition**

Maximum system voltage	1000V
Rated current of serial fuse	15A
Maximum front load	5400Pa (112 lb/ft <sup>2</sup> )
Maximum back load	2400Pa (50 lb/ft <sup>2</sup> )
Operating temperature range	-40~+85°C
Module Standard	A

**Module Dimension: (unit: mm)**

