

48V100Ah家庭储能电池/48V100Ah Home Energy Storage Battery

SNE-48100- I



产品参数/Parameters

产品型号/Product model	SNE-48100- I / II / III
产品规格 / Product specification	51.2V100Ah
标称电压/Nominal voltage	51.2V
标称容量/Nominal capacity	100Ah
电芯类型/Cell type	磷酸铁锂(LFP)
标准充电电压/Standard charge voltage	58.4V
最大充电电流/Max discharge current	100A
放电截止电压/Discharge cut-off voltage	40V
最大放电电流/Max discharge current	100A
电量显示/Display	LCD(可选Optional)
通讯接口/Communication interface	RS485、RS232、CAN(可选Optional)
循环寿命/Cycle life	≥3000周(80%DOD)
充电温度范围/Charge temperature range	0~65°C
放电温度范围 /Discharge temperature range	-20~65°C
颜色/Colour	白(White)/黑白(Black and white)
尺寸/Dimensions	390×175×600MM
重量/Weight	约50Kg
安装方式/Installation method	壁挂式(Wall mounted)

SNE-48100- I



SNE-48100- II



SNE-48100- III



比能量高

Higher specific energy



安装方便

Easy to install



循环寿命长

Long cycle life



支持并网使用

Support parallel operation



环保无污染

Environmental protection and no pollution



支持深度定制

Support deep customization

48V100Ah家庭储能电池/48V100Ah Home Energy Storage Battery

SNE-48100-IV



产品参数/Parameters

产品型号/Product model	SNE-48100-IV
产品规格 / Product specification	51.2V100Ah
标称电压/Nominal voltage	51.2V
标称容量/Nominal capacity	100Ah
电芯类型/Cell type	磷酸铁锂(LFP)
标准充电电压/Standard charge voltage	58.4V
最大充电电流/Max discharge current	100A
放电截止电压/Discharge cut-off voltage	40V
最大放电电流/Max discharge current	100A
电量显示/Display	LCD(可选Optional)
通讯接口/Communication interface	RS485、RS232、CAN(可选Optional)
循环寿命/Cycle life	≥3000周(80%DOD)
充电温度范围/Charge temperature range	0~65°C
放电温度范围 /Discharge temperature range	-20~65°C
颜色/Colour	白(White)/黑白(Black and white)
尺寸/Dimensions	436×185×720MM
重量/Weight	约46Kg
安装方式/Installation method	壁挂式(Wall mounted)



比能量高

Higher specific energy



安装方便

Easy to install



循环寿命长

Long cycle life



支持并网使用

Support parallel operation



环保无污染

Environmental protection and no pollution



支持深度定制

Support deep customization

