


EN156P-120- 270/275/280/285W







Polycrystalline Solar Module 120 Half-Cell Series

ABOUT ECONESS ENERGY

Established in 2009 by Jiangsu Huadong Group (founded in 1997), Econess Energy is a world's leading solution provider for solar energy. With annual production capacity of 800MW cells and 1.2GW modules. Econess Energy now distributes its PV products to over 36 countries with cumulative module shipment of 3GW. As a strong, bankable partner, we are committed to building strategic, mutually beneficial collaboration with installers and developers.



KEY FEATURES

-  **Maximize limited space**
Half cell structure technology (low resistance characteristics), more Internal reflection, Module maximum power output 285W
-  **Excellent Anti-PID performance**
2 times of industry standard Anti-PID test by TUV
-  **Lower temperature coefficients**
Enhance power generation
-  **Significantly reduce the hot spot effect**
Unique circuit design significantly reduces hot spot temperature and power loss
-  **Certified to withstand the most challenging environmental conditions**
2400 Pa wind load · 5400 Pa snow load · 25mm hail stones at 82 km/h
-  **IP68 junction box**
The highest waterproof level

SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 1703
- ISO 9001 : 2015 Quality Management System
- ISO 14001 : 2015 Environment Mangement System
- OHSAS 18001 : 2007 Occupational Health and Safety Management System




QUALITY WARRANTY

Econess Energy guarantees that defects will not appear in materials and workmanship defined by IEC61215, IEC61730 or UL1703 under normal installation, use and maintenance as specified in Econess Energy's installation manual for 10 years from the warranty starting date.

PERFORMANCE WARRANTY

Polycrystalline Solar Module



ELECTRICAL PARAMETERS

Performance at STC (Power Tolerance 0 - +3%)

Maximum Power(Pmax/W)	270	275	280	285
Operating Voltage (Vmpp/V)	31.35	31.71	32.05	32.33
Operating Current(Imp/A)	8.62	8.68	8.75	8.82
Open-Circuit Voltage (Voc/V)	38.51	39.68	39.02	39.31
Short-Circuit Current(Isc/A)	9.09	9.16	9.24	9.30
Module Efficiency η_m (%)	16.25	16.55	16.85	17.15

Performance at NMOT

Maximum Power(Pmax/W)	199	203	207	210
Operating Voltage(Vmpp/V)	28.83	29.12	29.37	29.65
Operating Current(Imp/A)	6.91	6.98	7.05	7.09
Open-Circuit Voltage(Voc/V)	35.47	35.63	35.93	36.18
Short-Circuit Current(Isc/A)	7.37	7.43	7.50	7.54



STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5

NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

MECHANICAL SPECIFICATION

Cell Type	Half-Cell Poly
Cell Dimensions	6inch
Cell Arrangement	120(6*20)
Weight	20kg(44.09lbs)
Module Dimensions	1675*992*35mm(64.96*39.06*1.38inches)
Cable Length	300mm(11.81inch)
Cable Cross Section Size	4mm ² (0.006sq.in)
Front Glass	3.2mm High Transmission, Tempered Glass
No.of Bypass Diodes	3/6
Packing Configuration (1)	30pcs/Pallet,840pcs/40hq
Packing Configuration (2)	30pcs+4pcs/Pallet, 896pcs/40hq
Frame	Anodized Aluminium Alloy
Junction Box	IP68

I-V CURVE




OPERATING CONDITIONS

Maximum System Voltage	1000V/DC(IEC)/1500V/DC(IEC)
Operating Temp	-40°C~+85°C
Maximum Series Fuse	15A/20A
Static Loading	5400Pa
Conductivity at Ground	$\leq 0.1\Omega$
Safety Class	II
Resistance	$\geq 100M\Omega$
Connector	MC4 Compatible

TEMPERATURE COEFFICIENT

Temperature Coefficient(Pmax)	-0.40%/°C
Temperature Coefficient(Voc)	-0.31%/°C
Temperature Coefficient(Isc)	+0.06%/°C
NMOT	45±2°C

TECHNICAL DRAWINGS



Econess Energy Co., Ltd.

58 Haida Road, Huashi, Jiangyin, Jiangsu, P.R. China 214421 +86-510-86076868 sales@eco-pv.com www.eco-pv.com

* This is preliminary datasheet and for reference only. The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. Econess Energy reserves the right to make necessary adjustment to the information described herein at any time without further notice.