

High Efficiency PV Modules / Solar Panels

FEATURES

- Product Warranty: 2 Year full Quality Warranty / 10- Year Limited Power Performance Warranty
- ◆ Cell Type: MonoCrystalline Silicon Photovoltaic
- Panel Construction: High-Efficiency Design Minimizes
 Weight While Providing a Durable Protective Environment for the Solar Cells
- Weatherproof: Front & Rear Surfaces and Junction Box Completly Sealed From Moisture with Silicone Sealant
- Meets IP65 Requirements: Totally Protected again Dust;
 Protected against Low-Pressure Jets of Water from all Directions.
- Certifications: ISO 9488 (solar Energy pending), ISO 9001:2008, IEC 61730 (Module Safety - Pending)

APPLICATIONS

- Secondary Home Power System / Remote Power Electrical Power Back-Up System
- ♦ On-Grind Commercial / Industrial Rooftops
- Off-Grid Power System
- Marine & Boating
- Recreational vehicle or Motor Homes / Cabins
- ► Battery Charging
- Pumps / Pool Heating
- Beacons / Satellite Dishes



SLR-PNL-300W-301E

Peak Output Power (Pmax)	300W
Power Tolerance Range	0- +5W
Open Circuit Voltage(Voc	c) 44.6V
Max.Power Voltage(Vmp)	36.1V
Short Circuit Current(Isc)	8.87A
Max.Power current(Imp)	8.31A
Wind Resistance	3800 Pa
Max. System voltage	1000V
Max.Series Fuse Rating	15A
Weight	23Kg
Module Application	Class A
Dimension	1950× 992 × 40mr

Shaan Tech

Factory: Shaan Technologies private Limited,
Plot No 22, Sector C3, Export Processing Zone
Karachi , Pakistan

Phone: +92-21-35080954 Fax: +92-21-35080957 City Sales office: Shaantech Energy Solutions (Pvt) Limited 47/H-1, Block 6, P.E.C.H.S., Karachi.

E-mail: info@shaantech.com, Sales-admin@shaantech.net

Website: www.shaantech.com

To order ShaanTech Solar products, Please Call our Sales office or contact the Distributor/Sales Representative in your area.

Visit our website to find your local Distributor or Representative from our Nationwide network:

www.shaantech.com