





All the parameters are specified at 25 ° C, 1000 w/m2 under the condition of light intensity and hold AM1.5 STC test

STC		Electrical performance parameter				NOCT		JD365MP6P	JD370M6P
Model number		JD355M6P	JD360M6P	JD365M6P	JD370M6P	The most powerful	Pm(W)	268.3	272.0
Component power range	(W)	355≤Pm<360	360≤Pm<365	365≤Pm<370	370≤Pm<375	Maximum working voltage	Vm(V)	38.1	38.2
The most powerful	Pm(W)	355	360	365	370	Maximum working current	Im(A)	7.85	7.93
Maximum working voltage	Vm(V)	39.0	39.2	39.3	39.4	The open circuit voltage	Voc(V)	36.1	36.2
Maximum working current	Im(A)	9.10	9.18	9.29	9.39	Short circuit current	Isc(A)	7.43	7.51
The open circuit voltage	Voc(V)	47.7	47.9	48.0	48.3				
Short circuit current	Isc(A)	9.63	9.70	9.74	9.84	Nominal battery temperature			
The efficiency of the component	(%)	18.3	18.6	18.8	19.1				
Power temperature coefficient	(%/°C)			-0.380					
Open circuit voltage temperature coefficient	(%/°C)			-0.286					
Short circuit current temperature coefficient	(%/°C)			0.067					
The AAA solar simulator (IEC 6094-4), the electrical performance data test uncertainty is between plus or minus 3%									

电流-电压曲线 (JD360M6P-36)



功率-电压曲线 (JD360M6P-36)



The limit parameter

Insulation voltage	6000/8000V
Working temperature (°C)	-40~+85
Maximum system voltage (V DC)	1000/1500
Maximum fusing current (A)	15
Maximum load	5400Pa(112.78lb/ft²)


The mechanical parameters

Diameter and length of cable models	4mm² ,TUV , 1000mm
Terminal type	Matching MC4 sub
The number of battery sheets and the columns	72 pieces of Single crystal cell (6x10)
The battery size (mm)	156.75x156.75
Component size (mm)	1956x992x40
The component weight (Kg)	22.5
The number of water holes on the border	16
Glass model and thickness	Low iron high penetration 3.2mm toughened glass

Packing configuration

Packing configuration	27PCS/carton
Pallet loading	54PCS/Joe
Container load	648 pieces /40 feet high cabinet
Packing configuration	27PCS/carton

The product specifications can be changed without prior notice.



35