



Solar Photovoltaic Modules

NEASE Solar Photovoltaic Module Specification Data

Module Type	24V/220WP	24V/240WP	24V/250WP
Max. Power	220WP	240WP	250WP
Cell Type	Poly/Mono Crystalline Silicon Solar Cells		
No. Of Cell	72 Cell		
Max. System Voltage	1000V		
Power Tolerance	± 3%.		
Surface Maximum Load Capacity	60m/s(200kg/sq.m)		
Weight	18.5 kg		
Glass Dimensions	1645 mm X 985 mm X 3.2 mm		
Electrical Characteristic			
Open Circuit Voltage(Voc)	44V	44V	44V
Short Circuit Current(Isc)	6.70	7.30A	7.60A
Max. Power Voltage(Vmax)	36V	36V	36V
Max. Power Current(Imax)	6.15	6.70A	7.00A
Temp Coefficiencies Of Isc	20µA/°C/Cell area/C_P		
Temp Coefficiencies Of Voc	-2.2mv/°C/C_S		
Temp Coefficiencies Of Pm	-0.44%/°C		
Cell Efficiency (%)	>15%		
Module Efficiency	>13%	>14.5%	>15%
Operating Temperature	-40 to +85°C		



Features and Benefits

- ❖ Cells are laminated with EVA, TPT and tempered glass ensuring long life and the most stringent safety requirements For High voltage operation.
- ❖ Anodized aluminum frame with convenient mounting slots.
- ❖ Nominal 6VDC/ 12V DC / 20V / 24V DC for standard output.
- ❖ We are specialized in 18, 36, 54, 60, 72 cells solar modules.
- ❖ We are specialized in making black and transparent back-sheet solar module as well.
- ❖ Withstand high wind pressure and snow load.
- ❖ Output power tolerance of ± 3%.
- ❖ High efficiency solar cells.



*Conditions:(STC):Irradiance:1000W/m²,spectral distribution AM1.5,Cell temperature:25°C

Module Dimensions



Certification



MNRE
Channel
Partner



* NEASE reserves the right to amend the above specification without prior notice.

NEETY EURO-ASIA SOLAR ENERGY

B/4/1 GIDC Electronics Estate Sector – 25 Gandhinagar - 382024 Gujarat , India

Tel : +91-79-23287395,23287396 Fax : +91-79-23287394

Email: sales@nease.in & info@nease.in

Web Site: www.nease.in