



JC-410-72MDX9

410W 144cells

High Efficiency Half-Cell Mono PERC Module



Half-cut cell technology
New circuit design,
lower internal current,
lower Rs loss



Special circuit design
with much lower hot spot
temperature



Fire safety
(Class C, certified to TÜV
Rheinland and Rheinland
test standards)



Resistance to power
attenuation passed TÜV
Rheinland system voltage
endurance test




Resistance to salt-spray
corrosion
(IEC61701, certified to TÜV
Rheinland test standard)



100% double EL test
enabling remarkable
reduction of hidden crack
rate of modules

LINEAR PERFORMANCE WARRANTY



COMPREHENSIVE CERTIFICATES



ISO 9001: Quality Management System
ISO 14001: Environmental Management System Standard
OHSAS 18001: International Occupational Health and
Safety Assessment System Standard

PRODUCT INSURANCE



Product quality
& process guarantee



Linear power
guarantee

JC-410-72MDX9 144cells

ELECTRIC CHARACTERISTICS

Model of modules	JC-410-72MDX9 JC-410-72MDX9H	
	STC	NOCT
Maximum power — P_{mp} (W)	410	309
Open-circuit voltage — V_{oc} (V)	50.0	47.7
Short-circuit current — I_{sc} (A)	10.25	8.27
Maximum power voltage — V_{mp} (V)	42.3	40.2
Maximum power current — I_{mp} (A)	9.70	7.69
Module efficiency — η_m (%)	20.38%	
Power tolerance (W)	(0,+5)	
Maximum system voltage (V)	1000V/1500V	
Maximum rated fuse current (A)	20	
Current operating temperature (°C)	-40~+85 °C	

STC (Standard Testing Conditions): Irradiance 1000W/m², Cell Temperature 25 °C , Spectra at AM1.5

NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient Temperature 20°C , Spectra at AM1.5, Wind at 1m/S

STRUCTURAL CHARACTERISTICS

Module dimensions (L*W*H)	2008 x 1002 x 40mm
Weight	22.5 kg
Number of half-cells	144 cells (6x24)
Cell	PERC Monocrystalline 158.75x79.38mm
Glass	Tempered, 3.2mm AR, High transmittance, Low iron
Frame	Anodized aluminum alloy
Junction box	IP67
Output wire	4.0 mm ² , wire length: 1200mm or Customized Length
Connector	MC4 Compatible
Mechanical load	5400 Pa


TEMPERFORMANCE RATINGS

Temperature coefficient (P_{max})	-0.37 %/°C
Temperature coefficient (V_{oc})	-0.29 %/°C
Temperature coefficient (I_{sc})	+0.05 %/°C
Nominal operating cell temperature	45±2 °C


PACKAGING CONFIGURATION

Container	20GP	40HQ
Quantity/pallet	26	27
Pallets/container	10	22
Quantity/container	260	660

MODULE DIMENSIONS (mm)



Current-Voltage & Power-Voltage Curves (390W)



Temperature Dependence of I_{sc} , V_{oc} , P_{max}

