

Better Technology Group Limited

Single battery directly drive 10KW



BMS Self-developed



Driven 10KW Inverter



Compatible with Mainstream inverters



Bluetooth (BT)



Communication Protocol Customization



LOGO Customization



3000A High Current Terminal



Load-bearing Casters Easy to Move



www.better-tech.net

Standing Type LiFePO4 Battery

Battery Style	48V300Ah	51.2V300Ah	48V400Ah	51.2V400Ah	48V500Ah	51.2V500Ah
Nominal Voltage	48.0V	51.2V	48.0V	51.2V	48.0V	51.2V
Rated Capacity	300Ah		400Ah		500Ah	
End-of-charge Voltage	54.0V	58.0V	54.0V	58.0V	54.0V	58.0V
End-of-discharge Voltage	39.0V	40.0V	39.0V	40.0V	39.0V	40.0V
Standard Charge Current	100A					
Max. Charge Current	200A					
Standard Discharge Current	100A					
Max. Discharge Current	200A					
Max. Peak Current	300A					
Communication	RS485/CAN/BT (optional)					
Charge/Discharge Interface	M8 Terminal					
Communication Interface	RJ45					
Shell Material/Color	Metal/White (color optional)					
Size	370*330*800mm		475*190*315mm		475*370*315mm	
Weight	138kg (about)	140kg (about)	173kg (about)	175kg (about)	218kg (about)	220kg (about)
Work Temperature Range	Charge: 0°C-50°C Discharge: -15°C-60°C					

*THE PARAMETERS ARE FOR REFERENCE ONLY. THE ACTUAL PRODUCT SHALL PREVAIL. SUPPORT CUSTOMIZATION, AND ON-DEMAND CUSTOMIZATION

www.better-tech.net