


## NEOSUN™ MaxPower 60

NEOSUN™ MaxPower is the series of highly efficient and robust solar panels with advanced PERC technology.

This is the next-generation technology built on NEOSUN's unique manufacturing process that ensures unparalleled quality control for every component of the module. These panels have high system energy yield even at low irradiance and low NOCT.



22.4%

### EXCELLENT CELLS EFFICIENCY

Advanced 5BB solar cells with PERC technology provide efficiency up to 22.4% (up to 19.9% module efficiency)



Weak Sunlight

### EXCELLENT WEAK LIGHT PERFORMANCE

Solar modules from NEOSUN Energy have excellent weak light performance (morning, evening and cloudy days)

+3%

### POSITIVE POWER TOLERANCE


Guarantee from 0 to +3% as power tolerance, you can obtain more power than conventional output



### SAND AND SALT PROTECTION

Reliable quality leads to a better sustainability even in harsh environment like desert or coastline

35mm



Ultrathin


### PANEL THICKNESS

The latest technologies allow us to make thin and light solar modules. Easy installation and transportation



### HIGH WIND AND SNOW RESISTANCE

NEOSUN Energy modules withstand snow load of up to 550 kg/m<sup>2</sup> and wind speed of up to 162km/h




For a period of twenty-five (25) years commencing on the Warranty Start Date, loss of power output of the nominal power output measured at Standard Test Conditions (ST C) for the Product(s) shall not exceed:

1. For Polycrystalline Products: 2% in the first year, thereafter 0.67% per year, ending with 82% in the 25th year after the Warranty Start Date.
2. For Monocrystalline Products: 3% in the first year, thereafter 0.67% per year, ending with 81% in the 25th year after the Warranty Start Date.

The Warranty Start Date shall be defined as the date of the Bill of Lading date

### I-V curves

I-V Curves of PV module NEOSUN 300W at different light power




### Electrical characteristics

Solar cells:	Mono PERC 60 cells 5BB, 6 inch, 6x10 pcs		
Max Power	315W	325W	330W
Power Tolerance	0 to +8W		
Voltage at Pmax (Vmp)	33.2V	33.6V	33.8V
Current at Pmax (Imp)	9.49A	9.67A	9.76A
Open-Circuit Voltage (Voc)	40.6V	41.3V	41.6V
Short-Circuit Current (Isc)	10.05A	10.23A	10.30A
Module Efficiency	18.88%	19.48%	19.78%
Max-System Voltage (VDC)	1000V(IEC), 600V(UL)		
No. of Bypass Diodes (pcs.)	3		
Max Series Fuse (A)	15A		
Temperature Coefficient of Pmax	-0.40% / °C		
Temperature Coefficient of Voc	-0.29% / °C		
Temperature Coefficient of Isc	0.05% / °C		
Nominal Operating Cell t°C	45 ± 2°C		

\*STC Conditions (1000W/m2; 1.5 AM and 25°C Cell temperature)

### Dimensions



### Mechanical Characteristics

Cable type, Diameter and Length	Ø =4mm <sup>2</sup> , L=900±5mm
Type of Connector	Compatible type MC4
Dimension AxBxC	1665x1002x30mm
Weight	19 kg
Front Glass	Tempered with AR coating
Junction Box (protection degree)	IP67 Rated
Frame	Clear anodized aluminum alloy

### Qualification Test Parameters

Dielectric Insulation Voltage	6000VDC max
Operating Temperature	-40°C to +85°C
Max load	5400Pa
Hailstone impact	25mm at 23m/s
Fire safety class	Class C

### Packaging Configuration

Container	20'GP	40'HQ
Pieces per pallet	35	35
Pallets per container	12	28
Pieces per container	420	980

**Caution: read safety and installation instructions before using this product**