

CEC6-72MH


Mono-crystalline Solar Panel with Multi-busbar and Half-cut 72 Cells

350~385W

POWER OUTPUT RANGE

17.6%~19.4%

MODULE EFFICIENCY



CECEP Solar Energy Technology (Zhenjiang) Co., Ltd. was established in August 2010 with a registered capital of 351million Yuan. It is the subsidiary of CECEP Solar Energy Co., Ltd.—a large size state-owned enterprise, mainly specialized in the research, manufacture and sales of crystalline silicon solar cells and modules.

 **中节能太阳能科技（镇江）有限公司**
 CECEP Solar Energy Technology (Zhenjiang) Co.,Ltd.

ADD: No.9,Beishan Road,New District,Zhenjiang, jiangsu,
 China 212132

Tel: +86-511-8559 7719

Fax: +86-511-8558 7711

Web: www.cecpsolar.com

Stock code: SZ000591 太阳能



WeChat public

Product Features



Module can withstand snow pressure up to 5400Pa,
 Module can withstand wind pressure up to 2400Pa;



Guaranteed power output :0~+5W;



With high-performance in weak light conditions
 (on cloudy days, mornings and evenings);



Obtaining International independent certification
 body certifications




ISO9001, ISO14001 and OHSAS18001 International
 Standards: Management systems of quality, environment,
 vocational health and safety

Quality Warranty

- Product materials and processes warranty for 10 years;
- No less than 90% power output within 12 years;
- No less than 80% power output within 25 years.

Linear Performance Warranty



Certifications



Module Parameter

Electrical Characteristics	CEC6-72-350MH/ CEC6-72-350MHV	CEC6-72-355MH/ CEC6-72-355MHV	CEC6-72-360MH/ CEC6-72-360MHV	CEC6-72-365MH/ CEC6-72-365MHV	CEC6-72-370MH/ CEC6-72-370MHV	CEC6-72-375MH/ CEC6-72-375MHV	CEC6-72-380MH/ CEC6-72-380MHV	CEC6-72-385MH/ CEC6-72-385MHV
Max Power(Wp)	350	355	360	365	370	375	380	385
Max-Power Voltage Vmp(V)	39.20	39.36	39.57	39.72	39.88	40.03	40.22	40.40
Max-Power Current Imp(A)	8.93	9.02	9.10	9.19	9.28	9.37	9.45	9.53
Open-Circuit Voltage Voc(V)	46.33	46.59	46.87	47.13	47.38	47.65	47.91	48.17
Short-Circuit Current Isc(A)	9.34	9.44	9.53	9.63	9.73	9.83	9.93	10.03
Max-system Voltage Vdc(V)	1000/1500	1000/1500	1000/1500	1000/1500	1000/1500	1000/1500	1000/1500	1000/1500
Module efficiency(%)	17.6%	17.9%	18.1%	18.4%	18.6%	18.9%	19.2%	19.4%
Power Tolerance(W)	0/+5W	0/+5W	0/+5W	0/+5W	0/+5W	0/+5W	0/+5W	0/+5W

All specified Parameters are at STC 25°C Ambient, 1000W/m² irradiance and AM1.5

Physical Parameter

Cell Size	156.75 × 78mm, 144pcs, Monocrystalline silicon(12 × 12)
Glass, Type and Thickness	High Transmission, Low Iron, Tempered Glass 3.2mm
Frame & No. of waterspout	Anodised aluminium & 20
Junction Box	IP 68 rated

Mechanical Characteristics

Dimension	2000*992*40*35mm
Mounting hole size	800*942, 1300*942mm
Cable Length	300mm
Weight	22.2Kg

Temperature Coefficient

Nominal Module Operating Temperature (NMOT)	42°C ± 2°C
Temperature coefficient of Pmax (δ (%/°C))	-0.38
Temperature coefficient of Voc (β (%/°C))	-0.29
Temperature coefficient of Isc (α (%/°C))	0.04


Packaging Configuration

Flatcar	Pieces per case	32 pcs/case
	Quantity per pallet	2 case/pallet
40 Feet Container	Pieces per case	30 pcs/case
	Quantity per pallet	2 case/pallet
	Pieces per container	660 pcs/40' HQ


Limit Parameters

Operating temperature	-40°C to +85°C
Maximum fuse rated current	15A

Technical Drawings



I-V Curve (350W)



CECEP Solar Energy Technology(Zhenjiang)Co.,Ltd.

Sales Hotline: +86-511-85597719 Sales E-mail: marketing@cecsec.cn
www.cecpsolar.com

Proclamation: The company reserves the final right for explanation on any of the information presented.
This data sheet specifications are subject to change without prior notice.
May 2019 EDITION