


eArc

SMA310M-6X10DW

310 Watt

60 Cell Monocrystalline Module



Ultra-light: Glass free module weighs 8.1 kg, 60% lighter than conventional glass modules.



Fast-Installation: Ease of handling results in shorter time on roof and streamlined safety management.



No Light Pollution: Glass-free design significantly reduces light pollution.



Durable: eArc is the first glassless module to pass the same durability tests as conventional glass modules, including IEC 61215:2016, IEC61730:2016 and UL1703 (USA). eArc has also passed PID, salt mist and ammonia corrosion tests.

POWER OUTPUT RANGE 305~310 W

POWER TOLERANCE 0-5 W

10 Year Product Warranty

25 Year Linear Power Warranty



www.sunman-energy.com




ULTRA-LIGHT & FLEXIBLE SOLAR PANEL


LINEAR PERFORMANCE WARRANTY

CAUTION: Read installation manual before using the product.


©2020 Sunman (zhenjiang) Co., Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.



DIMENSIONS




I-V CURVE (310)



TEMPERATURE CHARACTERISTICS

Nominal Module Operating Temperature(NOMT)	41±2 °C
Temperature Coefficient of P _{max}	-0.38 %/°C
Temperature Coefficient of V _{oc}	-0.28 %/°C
Temperature Coefficient of I _{sc}	0.020 %/°C



SMADW/IEC EN 2020B

ELECTRICAL CHARACTERISTICS

STC	SMA305M-6X10DW	SMA310M-6X10DW
Maximum Power (P _{max})	305	310
Maximum Power Voltage (V _{mp})	33.0	33.3
Maximum Power Current (I _{mp})	9.25	9.31
Open-circuit Voltage (V _{oc})	40.3	40.5
Short-circuit Current (I _{sc})	9.74	9.81
Module Efficiency (%)	18.3	18.6
Operating Temperature	-40 °C to 85 °C	
Maximum System Voltage	1000 V DC (IEC)	
Maximum Series Fuse Rating	20 A	
Application Class	Class A	
Power Tolerance	0/+5 W	

STC: Irradiance 1000W/m², Cell temperature 25°C, AM=1.5. Tolerances of P_{max}, V_{oc} and I_{sc} are within ±5%

NMOT	SMA305M-6X10DW	SMA310M-6X10DW
Maximum Power (P _{max})	229	233
Maximum Power Voltage (V _{mp})	30.5	30.7
Maximum Power Current (I _{mp})	7.51	7.59
Open-circuit Voltage (V _{oc})	37.4	37.6
Short-circuit Current (I _{sc})	7.96	8.04

NMOT: Irradiance 800W/m², Ambient temperature 20°C, AM=1.5, Wind speed 1 m/s.

MECHANICAL CHARACTERISTICS

Solar Cell	Monocrystalline silicon (158.75mm)
No. of Cells	60 (6×10)
Module Dimensions	1658×1005×35 mm
Weight	8.1kg
Backsheet	White
Frame	Anodized Aluminium Alloy
J-box	IP 68 rated
Output Cables	Photovoltaic technology cable 4.0 mm 2, (+)150 / (-)450 mm
Connector	MC4 compatible

PACKAGING CONFIGURATION

	20' GP	40' HC
Module per pallet	30	30
Pieces per container	180	780