




MODEL SV54 E



-  Premium quality
-  Power output range 240 - 255 Wp
-  100% EL testing
-  Mechanical load up to 5400 Pa
-  Low weight
-  Module efficiency up to 17,24 %
-  Positive power tolerance -0/+4,9 W
-  Made in Europe
-  IEC EN 61215 certified
-  IEC EN 61730 - 1 certified
-  IEC EN 61730 - 2 certified
-  PID test passed



Warranty:

- 10** years manufacturing defects
- 12** years limited, 90% output power
- 25** years limited, 80% output power



Certificate Number B A B T 8715

Electrical parameters at Standard Test Conditions (STC)				
MODEL	SV54-240 E	SV54-245 E	SV54-250 E	SV54-255 E
Peak power P_{MPP} [W]	240	245	250	255
Peak power tolerance [W]	-0/+4,9			
Short circuit current I_{SC} [A]	9,24	9,36	9,55	9,75
Open circuit voltage V_{OC} [V]	34,3	34,4	34,6	34,7
Rated current I_{MPP} [A]	8,60	8,72	8,93	9,13
Rated voltage V_{MPP} [V]	28,0	28,2	28,0	28,2
Current and voltage tolerance [%]	± 3			
Module efficiency [%]	16,23	16,56	16,90	17,24

STC: 1000W/m² irradiance, 25 °C cell temperature, AM1, 5 g spectrum according to EN 60904-3
Average relative efficiency reduction of 3,4 % at 200 W/m² according to EN 60904-1

Electrical parameters at Nominal Operating Cell Temperature (NOCT)				
MODEL	SV54-240 E	SV54-245 E	SV54-250 E	SV54-255 E
Peak power P_{MPP} [W]	174,42	178,36	181,39	186,69
Peak power tolerance [W]	-0/+4,9			
Short circuit current I_{SC} [A]	7,42	7,52	7,67	7,83
Open circuit voltage V_{OC} [V]	31,7	31,8	31,9	32,0
Rated current I_{MPP} [A]	6,80	6,90	7,07	7,23
Rated voltage V_{MPP} [V]	25,6	25,8	25,6	28,8

NOCT: module operating parameters at 800 W/m² irradiance, 20 °C ambient temperature, 1 m/s wind speed

MECHANICAL DATA	
Dimensions (H x W x D) [mm]	1492 x 992 x 35
Weight [kg]	17,5
Solar cells	54 cells, monocrystalline Si, 156 x 156 mm
Cells encapsulation	Ethylene vinyl acetate (EVA)
Front	Tempered solar glass, 3,2 mm
Back	Composite polyester Film
Frame	Anodized aluminium frame with twin-wall profile and drainage holes
Junction box	IP67 with 3 Bypass diodes,
Cable and connectors	Solar cable 4 mm ² , length 1000 mm, MC4 compatible connectors

NOTE: For extended models, SV54 E YYY, voltages and currents can vary where YYY is optional based on the chosen YYY variant (YYY = letter(s), F for black frame, B for silver frame and black backsheet, BC for full black module)

OPERATING CONDITIONS	
Temperature range [°C]	-40 to +85
Maximum system voltage [V]	1000
Max. series fuse rating	15A
Limiting reverse current	15A
Maximum surface load capacity	5400 Pa (Snow load)
Resistance against hail	Maximum diameter of 25 mm with impact speed 23 m/s

THERMAL CHARACTERISTICS	
Temperature coefficient of P_{MPP} [%/K]	-0,42
Temperature coefficient of I_{SC} [%/K]	0,05
Temperature coefficient of V_{OC} [%/K]	-0,33

