

## Solar Module (MTS 225M-24V – MTS 240M-24V)

Model Number	MTS225M-24V	MTS 230M-24V	MTS 235M-24V	MTS 240M-24V
Solar cell(156*156mm)	Mono	Mono	Mono	Mono
Maximum power (Wp)	<b>225Wp</b>	<b>230Wp</b>	<b>235Wp</b>	<b>240wp</b>
Maximum power voltage (V)	30.00	30.10	30.20	30.30
Maximum power current (A)	7.50	8.10	7.78	7.92
Open circuit voltage (V)	36.50	37.00	37.00	37.00
Short circuit current (A)	8.06	7.65	8.25	8.31
Cell Efficiency (%)	15.7%	16.0%	16.4%	16.7%
Module Efficiency (%)	13.2%	14.20%	14.5%	14.80%
Number of cells (Pc's)	60(6*10)			
Size of module (mm)	1652x992x50mm			
Maximum system voltage (V)	1000V			
Temperature coefficients of Isc (%)	+ 0.1/ °C			
Temperature coefficients of Voc (%)	-0.38/ °C			
Temperature coefficients of Pm (%)	-0.47/ °C			
Temperature coefficients of Im (%)	+0.1/ °C			
Temperature coefficients of Vm (%)	-0.38/ °C			
Temperature Range	-40°C——+80°C			
Surface Maximum Load Capacity	60m/s(200kg/m <sup>2</sup> )			
Allowable Hail Load	steel ball fall down from 1m height			
Weight per piece (kg)	19			
Junction Box Type	PV-RH0301( TUV )			
Connectors and Cables Type	With TUV certificate			
Length of Cables (mm)	900mm			
Output tolerance (%)	+/-3%			
Frame (Material, Corners, etc.)	Aluminum			
Standard Test Conditions	1000 w/m <sup>2</sup> AM1.5 25°C			
Warranty	5 years product warranty and 10years 90% + 25years 80% of power output			
FF (%)	≥72%			
Certificate	CE TUV IEC 61215 IEC 61730			
Quantity of one 40ft container	560pcs			