


## M60PCS-230W 225W 220W 215W Product Specification




- Industry leading module power output warranty
- International quality, safety and performance certifications
- Manufacturing facility certified to ISO9001 Quality Management System standards
- Beautiful appearance, good durability & easy installation
- Special design in accordance with requirements of customers

### CERTIFICATES




### WARRANTIES

- 10 years for product defects in materials & workmanship
- 10 years for 90% of warranted minimum power output
- 25 years for 80% of warranted minimum power output



25 years linear warranty




## Electrical parameters at Standard Test Conditions

(STC:AM=1.5, 1000W/m<sup>2</sup>, cells Temperature 25 °C)

## I-V CURVE

Typical Type	230W	225W	220W	215W
Max-Power (Pmax) w	230W	225W	220W	215W
Max-Power Voltage (Vmp)	30.13	29.95	29.77	29.58
Max-Power Current (Imp)	7.63	7.51	7.39	7.27
Open-Circuit Voltage (Voc)	36.9	36.68	36.46	36.23
Short-Circuit Current (Isc)	8.37	8.24	8.1	7.97
Max-System Voltage	DC1000V			
Cell efficiency (%)	16.5	16.1	15.8	15.4




## MECHANICAL DATA

Dimensions	1640*992*40mm
Weight	18kgs
Front Glass	3.2 mm tempered glass
	TUV (2Pfg1169:2007)
Output Cables:	4mm <sup>2</sup> (0.006 inches <sup>2</sup> ), symmetrical lengths 900 mm
Connectors:	MC4 compatible IP67
cell type:	Mono Crystalline silicon, 156mmx156mm
Number of cells:	60 cells in series

## TEMPERATURE CHARACTERISTICS

Temp.Coeff.of Isc(TK Isc)	0.037% / °C
Temp.Coeff.of Voc(TK Voc)	(-0.34%) / °C
Temp.Coeff of Pmax(TK Pmax)	(-0.48%) / °C
Operating Temperature	(-40~+85)°C
Nominal Operating Cell Temperature	45 ±2 °C

## DIMENSIONS AND STRUCTURE



## PACKING CONFIGURATION

Container	20'GP	40'GP	40'HQ
Pieces per Pallet	46	46	56
Pallets per Container	6	14	14
Pieces per Container	276	644	784

## TESTS, CERTIFICATIONS AND WARRANTIES

Standard tests	IEC 61215, IEC 61730
System certs	ISO 9001, ISO 14001
Certifications	TUV, CE, MCS, PV CYCLE, CEC, CHUBB
Extreme wind and snow loads testing	withstand extreme wind (3800 Pascal) and snow loads (5400 Pascal)
Positive tolerance	0~+3%
Junction Box	≥IP65 Rated
Warranties	10-year material and workmanship and 25-year output at least 80%.