

MONO-CRYSTALLINE

STM6-XXX/72 5BB Series 380W-400W

25

linear power
output warranty

12

Guarantee on product
Material and workmansh



5 Busbar Solar Cell

5 Busbar solar cell adopts new technology to improve the efficiency of modules, offers a better aesthetic appearance, making it perfect for rooftop.




High Efficiency

Higher module conversion efficiency (up to 19.66%) benefit from half cell structure (low resistance characteristic).



PID Resistance

Excellent Anti-PID performance guarantee limited power degradation for mass production.



Low-light Performance

Advanced glass and cell surface textured design ensure excellent performance in low-light environment.





Severe Weather Resilience

Certified to withstand: Wind load (2400 pascal) and snow load (5400 pascal).



Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance certified by TUV NORD.



Office(Changzhou): Room 1406, Block B, No. 88 Middle of Tongjiang RD(Wanda Plaza), Changzhou City, Jiangsu, China, 213001

Office(Nanjing): Room 1812, Suite A, No. 102 Jiangdong Road, Wanda Plaza, Nanjing City, Jiangsu, China, 210019

Factory(Chuzhou): Weisan Rd, Qianjiao Economic Development Area, Chuzhou City, Anhui Province, China, 239500

Factory(Thailand): 41/9 moo. 8 T. Bowin, A. Sriracha, Chonburi, Thailand, 20230

Tel: +86 25-86816810

+86 550-2309825

+86 519-89886585

Email: info@schutten.cn

Web: www.schutten-solar.com



Electrical Characteristics

Module Type	STM6-380/72	STM6-385/72	STM6-390/72	STM6-395/72	STM6-400/72
Maximum Power (Pmax)	380	385	390	395	400
Maximum Power Voltage (Vmp)	40.50	40.80	49.10	41.40	41.70
Maximum Power Current (Imp)	9.39	9.44	9.49	9.55	9.60
Open-circuit Voltage (Voc)	49.90	49.10	49.30	49.50	49.80
Short-circuit Current (ISC)	9.75	9.92	10.12	10.23	9.36
Module Efficiency STC (%)	19.16	19.42	19.67	19.92	19.58
Power Tolerance	0-+5W	0-+5W	0-+5W	0-+5W	0-+5W

 **STC: Irradiance 1000W/m²**
 **Cell Temperature 25±2°C**
 **AM=1.5**

Mechanical Characteristics

Cell Type	Mono-crystalline 158.75*158.75mm full
No. of Cells	72 (6*12)
Dimensions	1979*1002*40mm
Weight	22.5kgs
Front Glass	3.2mm High Transmission Low Iron Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67 Rated
Output cables	4mm ² cable 300mm or customized
Connector	MC4 Compatible
Hailstone Impact Test	80Km/h for 25mm ice ball

Thermal Characteristics


Nominal Operating Cell Temperature	45±2°C
Temperature coefficients of Pmax	-0.36%/°C
Temperature coefficients of Voc	-0.26%/°C
Temperature coefficients of Isc	+0.04%/°C

Packing Configuration

Container	40' HQ	Maximun Rating	Operating temperature	-40-+85°C
Pieces Per Pallet	27/5	Max System Voltage (IEC)	1500VDC	
Pallets Per CNTR.	24/11	Max System Voltage (BIS)	1500VDC	
Pieces Per CNTR.	708	Max Series Fuse Rating	20A	


Engineering Drawing

*All dimensions in mm



I-V Curves

Current- Voltage & Power-Voltage Curves 380W



Office(Changzhou):Room 1406,Block B,No.88 Middle of Tongjiang RD(Wanda Plaza),Changzhou City,Jiangsu,China,213001
 Office(Nanjing):Room 1812,Suite A,No.102 Jiangdong Road,Wanda Plaza,Nanjing City,Jiangsu,China,210019
 Factory(Chuzhou):Weisan Rd,Quanjiao Economic Development Area,Chuzhou City,Anhui Province,China,239500
 Factory(Thailand):41/9 moo.8 T.Bowin,A. Sriracha,Chonburi,Thailand,20230



Tel:+86 25-86816810
 +86 550-2309825
 +86 519-89886585
 Email:info@schutten.cn
 Web:www.schutten-solar.com