



Compact Size and – Easy Installation –

The module design enables quick installation



Multi-stage protection design enhances the safe storage; meets the standards of international safety certifications Expandable _____ at Need _____

EnerGuard units can be

combined to increase

energy capacity

トフ

 \mathbf{N}

Z




The compact structure achieves marketing-leading energy density



EnerGuard is cobalt-free and more environmentally sustainable





EnerGuard is covered by an industry-leading 10-year warranty



High _____ Reliability ____

EnerGuard's LFP-based battery with a long service life, high charge and discharge rate, and high energy transfer efficiency delivers high reliability, stability, durability and performance


BENEFITS


SELF-CONSUMPTION

Store solar energy generated from photovoltaic panels for the future use.

PEAK SHAVING

Peak shaving works to help solve the problem of power demand. Storing the power off-peak and using it on-peak can significantly lower the electricity bills.





	RESS-EnerGuard-3.3kWh	RESS-EnerGuard-6.5kWh
Battery Data		
Normal Voltage (V)	51.2	51.2
Normal Capacity (kWh)	3.3	6.5
Operating Voltage (V)	48~57.6	48~57.6
Charging /Discharing Current (A)	32/42.5	60/104.2
Rated Discharging Power (kW)	1.64	3
MAX Discharging Power (kW)	2.1	5
General Data		
Dimension (W*D*H)(mm)	440*400*131	440*600*131
Weight (kg)	30	58
IP Protection	IP20	IP20
Working Temperature (°C)	-10~+50	-10~+50
Storage Temperature (°C)	-20~+45	-20~+45
Features		
Cycle Life	>6000	> 6000
Parallel Connection	Max.6 packs	Max.2 packs
Communication Port	CAN2.0 /RS485	CAN2.0 /RS485
Warranty	10 years	10 years

Compatible Inverters Priority	Models
GoodWe	ES 3.6kW~5kW
Deye	SUN-6K-SG03LP1-EU
Ginlong	S5-EH1P(3~6)K-L
Growatt	SPF 5000 TLHVM-WPV;SPH3000TL BL-UP
Sungrow	SH5K-30

SHENZHEN ACE BATTERY CO., LTD.

Email: sales@acebattery.com Phone: +86 755 8887 8567 www.acebattery.com ©SHENZHEN ACE BATTERY CO., LTD. 05.2021 All rights reserved

