

## 柜式储能电池/Cabinet Type Energy Storage Battery

SNU-4850- I

### 产品参数/Parameters

产品型号/Product model	SNU-4850- I
产品规格 / Product specification	48V50Ah
标称电压/Nominal voltage	48V
标称容量/Nominal capacity	50Ah
电芯类型/Cell type	磷酸铁锂(LFP)
标准充电电压/Standard charge voltage	54.75V
最大充电电流/Max discharge current	50A
放电截止电压/Discharge cut-off voltage	37.5V
最大放电电流/Max discharge current	50A
电量显示/Display	LCD(可选Optional)
通讯接口/Communication interface	RS485, RS232, CAN(可选Optional)
循环寿命/Cycle life	≥3000周(80% DOD)
充电温度范围/Charge temperature range	0~65°C
放电温度范围/Discharge temperature range	-20~65°C
颜色/Colour	黑色(Black)
尺寸/Dimensions	442×400×133MM
重量/Weight	约26Kg
安装方式/Installation method	机柜式(Cabinet type)



比能量高

Higher specific energy



安装方便

Easy to install



循环寿命长

Long cycle life



支持并机使用

Support parallel operation



环保无污染

Environmental protection and no pollution



支持深度定制

Support deep customization

## 柜式储能电池/Cabinet Type Energy Storage Battery

SNU-4875- I

### 产品参数/Parameters

产品型号/Product model	SNU-4875- I
产品规格 / Product specification	48V75Ah
标称电压/Nominal voltage	48V
标称容量/Nominal capacity	75Ah
电芯类型/Cell type	磷酸铁锂(LFP)
标准充电电压/Standard charge voltage	54.75V
最大充电电流/Max discharge current	75A
放电截止电压/Discharge cut-off voltage	37.5V
最大放电电流/Max discharge current	75A
电量显示/Display	LCD(可选Optional)
通讯接口/Communication interface	RS485, RS232, CAN(可选Optional)
循环寿命/Cycle life	≥3000周(80% DOD)
充电温度范围/Charge temperature range	0~65°C
放电温度范围/Discharge temperature range	-20~65°C
颜色/Colour	黑色(Black)
尺寸/Dimensions	442×400×133MM
重量/Weight	约31.5Kg
安装方式/Installation method	机柜式(Cabinet type)



比能量高

Higher specific energy



安装方便

Easy to install



循环寿命长

Long cycle life



支持并机使用

Support parallel operation



环保无污染

Environmental protection and no pollution



支持深度定制

Support deep customization

