

# HIPerforma Series

144-CELL HALF CUT BIFACIAL  
MONOCRYSTALLINE SOLAR MODULE

# 390-410 Watt

STPXXXS - A72/Pnh+  
STPXXXS - A72/Pfh+



## Features



### High power output

Compared to normal module, the power output can increase 5W-10W



### High PID resistant

Advanced cell technology and qualified materials lead to high resistance to PID



### Excellent weak light performance

More power output in weak light condition, such as haze, cloudy, and morning



### Lower operating temperature

Lower operating temperature and temperature coefficient increases the power output



### Extended load tests

Module certified to withstand front side maximum static test load (5400 Pascal) and rear side maximum static test loads (3800 Pascal) \*



### Withstanding harsh environment

Reliable quality leads to a better sustainability even in harsh environment like desert, farm and coastline


Certifications and standards:  
IEC 61215, IEC 61730, conformity to CE



## Trust Suntech to Deliver Reliable Performance Over Time

- World-class manufacturer of crystalline silicon photovoltaic modules
- Unrivaled manufacturing capacity and world-class technology
- Rigorous quality control meeting the highest international standards: ISO 9001, ISO 14001 and ISO17025
- Regular independently checked production process from international accredited institute/company
- Tested for harsh environments (salt mist, ammonia corrosion and sand blowing testing: IEC 61701, IEC 62716, DIN EN 60068-2-68)\*\*\*
- Long-term reliability tests
- 2 × 100% EL inspection ensuring defect-free modules


## Industry-leading Warranty based on nominal power




- 97.5% in the first year, thereafter, for years two (2) through thirty (30), 0.5% maximum decrease from MODULE's nominal power output per year, ending with the 83% in the 30th year after the defined WARRANTY STARTING DATE.\*\*\*\*
- 12-year product warranty
- 30-year linear performance warranty

## High efficiency Bifacial half cut cell

By using high efficiency bifacial half cut cell and double glass technology, the frontside power can reach to 410 W, and the backside power generation can increase up to 25%.



5 BB



9 BB

## IP68 Rated Junction Box



The Suntech IP68 rated junction box ensures an outstanding waterproof level, supports installations in all orientations and reduces stress on the cables. High reliable performance, low resistance connectors ensure maximum output for the highest energy production.

\* Please refer to Suntech Standard Module Installation Manual for details. \*\*WEEE only for EU market.

\*\*\* Please refer to Suntech Product Near-coast Installation Manual for details. \*\*\*\* Please refer to Suntech Product Warranty for details.

### Electrical Characteristics

STC	STPXXS-A72/Pnh+ & STPXXS-A72/Pfh+				
Maximum Power at STC (Pmax)	410 W	405 W	400 W	395 W	390 W
Optimum Operating Voltage (Vmp)	41.1 V	40.9 V	40.7 V	40.5 V	40.3 V
Optimum Operating Current (Imp)	9.98 A	9.91 A	9.83 A	9.76 A	9.68 A
Open Circuit Voltage (Voc)	48.9 V	48.7 V	48.5 V	48.3 V	48.1 V
Short Circuit Current (Isc)	10.79 A	10.72 A	10.64 A	10.57 A	10.50 A
Module Efficiency	20.2%	20.0%	19.7%	19.4%	19.2%
Operating Module Temperature	-40 °C to +85 °C				
Maximum System Voltage	1500 V DC (IEC)				
Maximum Series Fuse Rating	20 A				
Power Tolerance	0/+5 W				

STC: Irradiance 1000 W/m<sup>2</sup>, module temperature 25 °C, AM=1.5;  
Tolerance of Pmax is within +/- 3% and tolerances of Voc and Isc are within +/- 5%.

NMOT	STPXXS-A72/Pnh+ & STPXXS-A72/Pfh+				
Maximum Power at NMOT (Pmax)	310.4 W	306.7 W	302.8 W	299.2 W	295.4 W
Optimum Operating Voltage (Vmp)	37.7 V	37.5 V	37.3 V	37.1 V	36.9 V
Optimum Operating Current (Imp)	8.24 A	8.18 A	8.12 A	8.06 A	8.00 A
Open Circuit Voltage (Voc)	45.9 V	45.7 V	45.5 V	45.4 V	45.2 V
Short Circuit Current (Isc)	8.70 A	8.65 A	8.58 A	8.53 A	8.47 A

NMOT: Irradiance 800 W/m<sup>2</sup>, ambient temperature 20 °C, AM=1.5, wind speed 1 m/s.

### Electrical Characteristics with Different Rearside Power Gain(Reference to 400 W Front)

Rearside Power Gain	5%	15%	25%
Maximum Power at STC (Pmax)	420 W	460 W	500 W
Optimum Operating Voltage (Vmp)	40.7 V	40.7 V	40.8 V
Optimum Operating Current (Imp)	10.32 A	11.30 A	12.28 A
Open Circuit Voltage (Voc)	48.5 V	48.5 V	48.6 V
Short Circuit Current (Isc)	11.17 A	12.24 A	13.30 A
Module Efficiency	20.7%	22.6%	24.6%

### Temperature Characteristics

Nominal Module Operating Temperature (NMOT)	42 ± 2 °C
Temperature Coefficient of Pmax	-0.37%/°C
Temperature Coefficient of Voc	-0.304%/°C
Temperature Coefficient of Isc	0.050%/°C


### Mechanical Characteristics

Solar Cell	Monocrystalline silicon 158.75 mm
No. of Cells	144 (6 × 24)
Dimensions	2028 × 1002 × 35 mm (79.8 × 39.4 × 1.4 inches)
Weight	27.0 kgs (59.52 lbs.)
Front Glass	2.0 mm (0.079 inches) semi-tempered glass
Frame	Anodized aluminium alloy
Junction Box	IP68 rated
Output Cables	4.0 mm <sup>2</sup> , (-)350 mm and (+)160 mm in length or customized length
Connectors	MC4 EVO2, Cable 01S
Refer. Bifaciality Factor	(70 ± 5)%


### Packing Configuration

Container	20' GP	40' HC
Pieces per pallet	31	31
Pallets per container	5	22
Pieces per container	155	682
Packaging box dimensions	2058 × 1130 × 1173 mm	
Packaging box weight	890 kg	

Information on how to install and operate this product is available in the installation instruction. All values indicated in this data sheet are subject to change without prior announcement. The specifications may vary slightly. All specifications are in accordance with standard EN 50380. Color differences of the modules relative to the figures as well as discolorations of/in the modules which do not impair their proper functioning are possible and do not constitute a deviation from the specification.



Current-Voltage & Power-Voltage Curve (410S)



### Dealer information

