

Controller & Inverter Device		SNS-0.5K15C
Appearance		
Rated capacity (KVA)		0.5
DC Input	Input nominal voltage(V _{DC})	24.0
	Low voltage protection	21.6
	Recovery voltage(V _{DC})	25.6
	Over-voltage protection	35
	Recovery voltage(V _{DC})	34
controller	Max input current	15A
	Charging mode	PWM
	Max open circuit voltage(V _{DC})	40
	Charging approach	2
	Over-charging protection(V _{DC})	28.8
	Recovery voltage(V _{DC})	28.4
AC Input	Input voltage (VAC)	170~255(±2%)
	Frequency (HZ)	50/60(±1%)
	Switching mode (optional)	Power grid as priority/inverter as priority
	Switching time (ms)	≤10
Inverter	Output power (KW)(liner load)	0.4
	Output waveform	Sine wave (liner load)
	Output voltage	220±5%(VAC)
	Output frequency	50/60(±3%)
	voltage (THD)	≤5%(liner load)
	Total harmonic distortion	≤3%
	100%~120% over-load	Shut off in 1min
	>120% over-load	shut off in 1s
	Static consumption	≤0.1A
	Dynamic response (1-100%)	5%
	Current peak factor	3:1
Peak efficiency	≥85%	
Protection	Low-voltage、over-voltage、over-load、short-circuit、overheating、false connection and etc	
Display	LCD/Digital display	
Communication	RS485(optional)	
Heat dissipation method	Forced-air colling	
Operating environment	noise(dB、1m)	≤50
	Ambient temperature(°C)	-20°C~+45°C
	Relative humidity	≤95%, non condensation
	Altitude	≤5000m(>1000m deated)

[Http://www.upsolarpower.com](http://www.upsolarpower.com)

Skype: guofen29790140

Mobile: 86-13665233012