

F2K_H8A / 144 cells

390W - 410 W

Mono-Crystalline PV Module


URE Peach module uses URE state-of -the art cell cutting technology, and advanced module manufacturing experiences.



Key Features



100% EL inline inspection
Better module reliability



Design for 1500 VDC
Reduce the system BOS effectively




Withstand heavy loading
front load 5400 Pa & rear load 2400 Pa



Excellent low light performance
3.5% relative eff. Reduction at low-irradiance (200W/m²)





URE

United Renewable Energy Co., Ltd.

Electrical Data

Model - STC		F2K390H8A	F2K395H8A	F2K400H8A	F2K405H8A	F2K410H8A
Maximum Rating Power (Pmax)	[W]	390	395	400	405	410
Module Efficiency	[%]	19.38	19.63	19.88	20.13	20.38
Open Circuit Voltage (Voc)	[V]	48.64	48.92	49.21	49.48	49.76
Maximum Power Voltage	[V]	40.42	40.65	40.87	41.09	41.29
Short Circuit Current (Isc)	[A]	10.15	10.22	10.29	10.36	10.43
Maximum Power Current	[A]	9.65	9.72	9.79	9.86	9.93

*Standard Test Condition (STC): Cell Temperature 25 °C, Irradiance 1000 W/m², AM 1.5

*Values without tolerance are typical numbers.Measurement tolerance: ± 3%

*Assembly in China

Mechanical Data

Item	Specification
Dimensions	2008 mm (L) ¹ x 1002 mm (W) ¹ x 40 mm (D) ² / 79.1" (L) ¹ x 39.4" (W) ¹ x 1.57" (D) ²
Weight	22.5 kg / 49.6 lbs
Solar Cell	144 half-cut monocrystalline 6" silicon cells
Front Glass	High Transmission Tempered glass,3.2mm thickness
Cell Encapsulation	EVA (Ethylene-Vinyl-Acetate)
Back Cover	Composite film, white
Fram	Anodized aluminium alloy
Fire Rating	CLASS C
Junction Box	Tian Sheng TS03-13B;Holysun S1,
Connectors	Tian Sheng TS02; Holysun C1 /C2
Packaging Configuration	(27+27+4) pcs / pallet, 638 pcs / 40' HQ container

¹ : With assembly tolerance of ± 2 mm [± 0.08"]

² : With assembly tolerance of ± 0.8 mm [± 0.03"]

Operating Conditions

Item	Specification
Mechanical Load (Test Load)	5400 Pa (Certified by TUV)
Maximum System Voltage	TUV 1500 VDC
Series Fuse Rating	15 A
Operating Temperature	-40 to 85 °C


Temperature Characteristics

Item	Specification
Nominal Module Operating Temperature	45°C ± 2°C
Temperature Coefficient of Isc	0.024 % / °C
Temperature Coefficient of Voc	-0.287 % / °C
Temperature Coefficient of Pmax	-0.393 % / °C


*Nominal module operating temperature (NMOT): Air mass AM 1.5, irradiance 800W/m², temperature 20°C, windspeed 1 m/s.

*Reduction in efficiency from 1000W/m² to 200W/m² at 25°C: 3 ± 2%.


Engineering Drawing (mm)



Dependence on Irradiance



Reliability with Warranty



Output warranty
25
Years

Product Guarantee
12
Years

For more information, please visit us at www.urecorp.com

United Renewable Energy Co., Ltd.

Assemble in China

Copyright © 2019 URE Corp. All rights reserved

Taipei Office

9F, NO. 295, Sec. 2, Tiding Blvd.,
Neihu Dist., Taipei 11493, Taiwan

Tel : +886-2-2656-2000

Fax : +886-2-2656-0593

e-mail : sales@urecorp.com

Headquarters

No. 7, Li-Hsin 3rd Road, Hsinchu Science Park
Hsinchu city 30078, Taiwan

Tel : +886-3-578-0011

Fax : +886-3-578-1255

URE_AUS_Peach_F2K_H8A_H1_3.2_40mm_WS_EN_200110