



M2 SERIES






AP72H 325~345W



M2 SERIES

LDK redefined the high-efficiency module series by integrating 157mm silicon wafers with multi-busbar and half-cut cell technologies. LDK module combined creative technology effectively and extremely improved the module efficiency and power output.

KEY FEATURES

-  Higher system voltages can effectively reduce BOS
-  Lower operating temperature and temperature coefficient, obtain higher profit
-  Significantly reduce the effect of hot spot temperature and shadow shielding
-  Better design for better mechanical load performance
-  Ease of use in more demanding environments

MANAGEMENT SYSTEM

- ISO9001:2015
- ISO14001:2015
- OHSAS18001:2007


PRODUCT CERTIFICATION



LDK is a leading manufacturer and service provider of professional pv cells and modules that can be widely utilized in residence, commerce and ground pv plant.

LDK provides PV products with exceptional power output and reliability by integrating rigorous design, advanced production technology and fully automatic production equipment. Strict quality control and test standards confirm its pursuit of high quality output.

WARRANTY



XinYu LDK Power Supply Technology Co.,Ltd

ADD: No. 1950 SaiWei Avenue, High-Tech, Industrial Development Zone, XinYu City, JiangXi Province, P.R. CHINA

ELECTRICAL PARAMETERS@STC AP72H-325~345

Max. Power Output Pmax (W)	325	330	335	340	345
Power Tolerance	0~3%	0~+3%	0~+3%	0~+3%	0~+3%
Max. Power Voltage Vmp (V)	37.75	38.11	38.38	38.60	38.86
Max. Power Current Imp (A)	8.61	8.66	8.73	8.81	8.88
Open Circuit Voltage Voc (V)	45.68	45.96	42.24	46.51	46.79
Short Circuit Current Isc (A)	9.14	9.20	9.46	9.57	9.68
Module Efficiency (%)	16.75	17.01	17.26	17.52	17.78

STC (Standard Test Condition): Irradiance 1000W/m², Cell Temperature 250C, Air Mass 1.5

ELECTRICAL PARAMETERS@NMOT

Max. Power Output Pmax (W)	244	247	250	254	258
Max. Power Voltage Vmp (V)	35.28	35.58	35.40	35.56	35.73
Max. Power Current Imp (A)	6.91	6.94	7.07	7.15	7.22
Open Circuit Voltage Voc (V)	42.86	43.09	43.37	43.62	43.89
Short Circuit Current Isc (A)	7.37	7.42	7.63	7.72	7.81

Nominal Module Operating Temperature (NMOT), Irradiance of 800W/m², Spectrum AM 1.5, Ambient Temperature 20°C, Wind Speed 1m/s

TEMPERATURE COEFFICIENTS

Temperature Coefficients of Pmp	-0.37%/°C
Temperature Coefficients of Voc	-0.31%/°C
Temperature Coefficients of Isc	+0.049%/°C

MECHANICAL PARAMETERS




Cell Type	Poly 157×157mm
Number of Cells	72pcs (6×12)
Dimensions (L*W*H)	1957×992×35mm
Weight	21.5kg
Frame	Anodized Aluminum
Junction Box	IP67, 3 bypass diodes
Cable, Length	4mm ² , 1000mm

OPERATING CONDITION

Maximum System Voltage(V)	1500 (DC)
Operating Temperature(°C)	-40~+85
Max. Wind Load / Snow Load(pa)	2400/5400
Max. Over Current(A)	20
Application Class	ClassA
Fire Rating	ClassC
NMOT(°C)	42±3


PACKAGE INFORMATION

Per Pallet	30/ 30+5pcs
40' HQ	780 (65×12) pcs



*No notice when product specifications change

Dealer information



XinYu LDK Power Supply Technology Co.,Ltd

ADD: No. 1950 SaiWei Avenue, High-Tech, Industrial Development Zone, XinYu City, JiangXi Province, P.R. CHINA
Email: modulesales@ldksolar.com