





Code	YGE6-200
Design Number	27002064E
Nominal Capacity (Ah)	200
Box Type / Number of Cells	GU / 3
Voltage (V)	6
Electrolite Type	Gel
Weight (kg) (+ - %5)	35,5
Dimensions (mm) L / W / H (H1-H2)	265/181/253-276 [+5/-1mm]
Terminal Type	Round Type (DIN 72311-4) + M8 Optional
Float Voltage	6,75 VDC @25°C
Cycle Voltage	7,35 VDC @25°C
Recommended Charging Current Limit (Ah)	20
Discharge Cut-Off Voltage %100 Depth of Discharge D.O.D.	1,75 VDC @ (A) <=0,2 C
Capacity C20 (Ah)	200,0
Capacity C10 (Ah)	190,2
Capacity C5 (Ah)	162,8
Capacity C3 (Ah)	155,0
Self Discharge	Less than %2 per month @25°C
Storage Time	6 months @25°C. Charge Recommended Before Using
Cycle Life DOD %80	650
Cycle Life DOD %50	1200
Cycle Life DOD %20	3200
Internal Resistance [miliohm]	4 @25°C








**Terminal Type A**  
DIN 72311-4 Round Type

**Layout (2)**





**Terminal Type S**  
(M-8 Optional)





**Yiğit Akü A.Ş.**

Organize Sanayi Bölgesi Oğuz Caddesi No: 2 Sincan / Ankara - TURKEY

Tel : +90 312 267 02 80 - Fax: +90 312 267 08 61 - 267 40 00

[endustriyel@yigitaku.com](mailto:endustriyel@yigitaku.com)

[www.yigitaku.com](http://www.yigitaku.com)