

## Mono-Crystalline



10BB technology decreases the distance between main bus bars and finger grid lines which reduces electric current lose and benefit to power increase.



10BB technology adopts a special round welding ribbon which effectively avoid solar cells cracks and micro cracks.



Sun Earth East solar modules are guaranteed to work for more than 25 years so as to guarantee investor's profit. The modules are proved that the power depreciation is less than 20% after 25 years working.




Superior loading capacity: snow pressure of 5400PA and wind pressure of 2400PA.



PID FREE.



Superior design: module efficiency is up to 21.38% with white EVA ( the maximum output power of 120pcs series is up to 605W ) , The power tolerance of module is 0/+5W.



## M9 Hi-Eff Mono Half Cells

**DXM9-60H 585W~605W**



# M9 Hi- Eff Mono Half Cells


## DXM9-60H 585W ~ 605W

### SPECIFICATIONS


|  | STC                   |        |        |        |        | NOCT    |         |         |         |         |
|--|-----------------------|--------|--------|--------|--------|---------|---------|---------|---------|---------|
|  | 585W                  | 590W   | 595W   | 600W   | 605W   | 585W    | 590W    | 595W    | 600W    | 605W    |
| Rated Power (Pmax):                          | 585W                  | 590W   | 595W   | 600W   | 605W   | 442.54W | 446.33W | 450.11W | 453.89W | 457.67W |
| Maximum Power (Pmax):                        | 585W                  | 590W   | 595W   | 600W   | 605W   | 442.54W | 446.33W | 450.11W | 453.89W | 457.67W |
| Rated Voltage at Pmax (Vmp):                 | 34.5V                 | 34.6V  | 34.7V  | 34.8V  | 34.9V  | 31.83V  | 31.92V  | 32.01V  | 32.11V  | 32.20V  |
| Rated Current at Pmax (Imp):                 | 16.96A                | 17.05A | 17.15A | 17.24A | 17.34A | 13.90A  | 13.98A  | 14.06A  | 14.13A  | 14.21A  |
| Open-circuit Voltage (Voc):                  | 41.4V                 | 41.5V  | 41.6V  | 41.7V  | 41.8V  | 38.72V  | 38.81V  | 38.90V  | 39.00V  | 39.09V  |
| Short-circuit Current (Isc):                 | 17.98A                | 18.08A | 18.17A | 18.26A | 18.36A | 14.62A  | 14.70A  | 14.78A  | 14.85A  | 14.93A  |
| Module Efficiency (ηm):                      | 20.7%                 | 20.8%  | 21.0%  | 21.2%  | 21.4%  |         |         |         |         |         |
| Maximum System Voltage:                      | 1500VDC               |        |        |        |        |         |         |         |         |         |
| Application Class:                           | Class A               |        |        |        |        |         |         |         |         |         |
| Fire Resistance Class:                       | Class C               |        |        |        |        |         |         |         |         |         |
| Maximum Over-Current Rating:                 | 30A                   |        |        |        |        |         |         |         |         |         |
| Operating Temperature:                       | 85% Rh, -40°C ~ +85°C |        |        |        |        |         |         |         |         |         |
| Maximum Snow Loads (front):                  | 5400Pa                |        |        |        |        |         |         |         |         |         |
| Maximum Wind Loads (front & back):           | 2400Pa                |        |        |        |        |         |         |         |         |         |
| Maximum Hailstone Impact (diameter @ 23m/s): | 25mm                  |        |        |        |        |         |         |         |         |         |

- STC: Irradiance 1000W/m<sup>2</sup>, Cell temperature 25°C, Air mass AM1.5 according to EN60904-3.
- NOCT: Irradiance 800W/m<sup>2</sup>, Ambient temperature 20°C/s, wind Speed 1m/s.
- Average efficiency reduction of 4.5% at 200W/ m<sup>2</sup> according to EN60904-1.

### I-V (605W)



### Temperature Dependence of Isc, Voc, Pmax




### Thermal Characteristics:

|  |           |
|--|-----------|
| Nominal Operating Cell Temperature (NOCT): | 43±2°C    |
| Temperature Coefficient of Pmax (γ Pmp):   | -0.34%/°C |
| Temperature Coefficient of Voc (β Voc):    | -0.25%/°C |
| Temperature Coefficient of Isc (α Isc):    | +0.04%/°C |


### Construction Characteristics:

|                                      |  |
|--------------------------------------|--|
| Front Cover :                        | low-iron tempered glass/3.2mm  |
| Cell:                                | 120 pcs mono-crystalline 210×105mm                                   |
| Anodized aluminum alloy Frame :      | ■ silver ■ black   |
| Junction Box (protection degree):    | IP68   |
| Cable (length/cross-sectional area): | Portrait 600mm/4mm <sup>2</sup><br>Landscape 1200mm/4mm <sup>2</sup> |
| Connector (protection degree):       | IP68   |
| Module Dimension (L×W×H):            | 2172×1303×35mm   |
| Weight:                              | 30.9±3% kg   |

### Dimensions (tolerance ±2mm)



### Warranty:



Please refer to Sun Earth East Solar Product Warranty for details.