POLYCRYSTALLINE SILICON | PHOTOVOLTAIC MODULES 320 W



About APS:

Australian Premium Solar (APS) is 100% Australian Owned managed and operated. APS supplies imported high quality renewable energy products Our solar panels are manufactured in accordance with APS's high standards of design and Quality Control Which ensure higher PV energy yields.


APS opened an advanced facility in Queensland, Australia for research and development and local testing of solar panels. The 2000 sq. mtr. facility is staffed by qualified engineers, who are dedicated to exploring ways to achieve the continuous improvement of our solar cells and solar modules.


12 Years Product Warranty* | 30 Years Performance Warranty*

91.2% Power Output Up To 12 Years

80.7% Power Output Up To 30 Years

ISO 9001: Quality Management System | CHUBB Insurance | PID Free







Australian Brand Manufactured in accordance with APS's high standards of design and Quality Control



Positive tolerance Positive tolerance of up to 4% delivers higher output reliability for our all modules.



High Model Output Highest conversion efficiency



EL Tested (ELECTRO LUMINESCENCE) 100% EL double inspection



Excellent module efficiency Solar cell efficiency up to 21.2% Module efficiency up to 18%



High performance Higher PV Energy yeilds even under low light and cloudy conditions



Reliability Premium quality raw material and advanced manufacturing processes guarantees the reliability of our modules



PID resistant and free of snail trails Increased module robustness to minimize micro-cracks



















ELECTRICAL TYPICAL VALUES

Model	
Maximum Power (Pmax)	
Maximum Power Voltage (Vmp)	
Maximum Power Current (Imp)	
Open Circuit Voltage (Voc)	
Short Circuit Current (Isc)	
Tolerance	
Module Efficiency	

APSP6-320/72
320 W
37.1 V
8.63 A
45.8 V
9.01 A
Positive only
16.2%

MECHANICAL CHARACTERISTICS

Dimensions	
Weight	

1960 x 990 x 35mm	
22.2 kg	


NOTE: STC: Irradiance 1000W/m2 Module Temperature 25°C AM = 1.5

TEMPERATURE CHARACTERISTICS		
NOCT (Nominal Operation Temperature)	: 47 <u>+</u> 2°C	
Temperature Coefficient of Voc (ß)	: -0.35%/°C	
Temperature Coefficient of Isc (a)	: +0.05%/°C	
Temperature Coefficient of Pmax (y)	: -0.45%/°C	


ABSOLUTE MAXIMUM RATING		
Parameter	Values	
Operating Temperature	From -40° to 85°	
Maximum Series Fuse Rating	15 A	
IEC Application Class	IEC 61215,IEC 61730,	
	IEC 61701, IEC 62804	
Maximum System Voltage	1000v DC (IEC 61215)	
	600v (UL 1703)	

MODULE CHARACTERISTICS Poly Solar Cells No. of Cells 72 Cells(12*6) Low iron, tempered glass, 3.2mm Glass Frame Anodized aluminum alloy IP65/67 rated Junction Box Cable & Plug Connectors $1.1 \text{ x } 4.0 \text{mm}^2 \text{ Mc4 compatible} / \text{IP } 67$ Maximum Snow Load 2400 Pascal Maximum Wind Load 5400 Pascal Hailstone Impact Test 80 km/h for 25mm ice ball

MODULE DIMENSION



I-V CURVE



Note:

- The specifications in this datasheet are subject to change without any notice.
- The electrical data given here is for reference purpose only.
- Please contact our sales team for any customized solutions.
- Please read safety and installation instructions before using the product.
- · Subject to Ahmedabad Jurisdiction.

*Warranty:

Please read APS India warranty documents thoroughly on http://australianpremiumsolar.co.in/warranty/

Corporate Office:

Australian Premium Solar (India) Pvt. Ltd., B-802, 8th Floor, Shapath Hexa, Nr. Sola Bridge, Opp. Gujarat High Court, S. G. Highway, Ahmedabad-380061. Gujarat (India).

M.: +91-76220-23258

Email: sales@australianpremiumsolar.co.in **Web:** www.australianpremiumsolar.co.in

Toll Free: 1800-313-5052

Factory-1:

Australian Premium Solar (India) Pvt. Ltd., Plot No. 143, Road No. 4A, GIDC-Kathwada, Ahmedabad-382430. Gujarat (India).



Factory-2: Australian Premium Solar (India) Pvt. Ltd., At & Post - Tajpur, N.H.-08, Ta - Prantij, Dist - Sabarkantha, Gujarat-383205 (India)