

RHI-(3-6)K-48ES-5G

Solis Energy Storage Inverters



360 degree

Features:

- ▶ Uninterrupted power supply, 20ms reaction
- ▶ 5kW backup power to support more important loads
- ▶ With shifting and peak shaving capabilities friendly to grid
- ▶ Multiple working modes to make maximize self-consumption, increase benefit
- ▶ Higher charge-discharge efficiency, improving the economic benefits
- ▶ Compatible with lithium & lead-acid batteries, increased more choice in different markets
- ▶ Fanless design, long lifespan
- ▶ Intelligent BMS function, improving battery's reliability
- ▶ With high-frequency isolation technology, making system safer and long lifespan
- ▶ 24-hour fully intelligent energy management, Real-time grasp of PV plant status
- ▶ Remotely control & upgrade function, making digital power plant maintenance at your fingertips



Model:

RHI-3K-48ES-5G

RHI-3.6K-48ES-5G

RHI-4.6K-48ES-5G

RHI-5K-48ES-5G

RHI-6K-48ES-5G

Datasheet

Model Name	RHI-3K-48ES-5G	RHI-3.6K-48ES-5G	RHI-4.6K-48ES-5G	RHI-5K-48ES-5G	RHI-6K-48ES-5G
Input DC (PV side)					
Recommended max. PV power	7kW	7kW	8kW	8kW	8kW
Max. input voltage			600V		
Rated voltage			330V		
Start-up voltage			120V		
MPPT voltage range			90-520V		
Max. input current			11A/11A		
Max. short circuit current			17.2A/17.2A		
MPPT number/Max. input strings number			2/2		
Battery					
Battery type			Li-ion/Lead-acid		
Battery voltage range			42 - 58V		
Battery capacity			50 - 2000Ah		
Max. charging power	3kW		5kW		
Max. charge/discharge current	62.5A/62.5A		100A/100A		
Communication			CAN/RS485		
Output AC (Back-up)					
Rated output power	3kW		5kW		
Max. apparent output power	4kVA		6kVA		
Back-up switch time			<20ms		
Rated output voltage			1/N/PE, 220/230V		
Rated frequency			50/60Hz		
Rated output current	13A		22A		
THDi			2% (linear load)		
Input AC (Grid side)					
Input voltage range			180-270V		
Max. input current			26.1A		
Frequency range			45-55 Hz/ 55-65 Hz		
Output AC (Grid side)					
Rated output power	3kW	3.6kW	4.6kW	5kW	6kW
Max. apparent output power	3.3kVA	4kVA	4.6kVA	5.5kVA	6kVA
Operation phase			1/N/PE		
Rated grid voltage			220/230V		
Rated grid frequency			50/60Hz		
Rated grid output current	13A	15.7A	20.9A	21.7A	26.1A
Max. output current	15.7A	17.3A	23A	23.9A	26.1A
Power Factor			>0.99 (0.8 leading - 0.8 lagging)		
THDi			<2%		
Efficiency					
Max. efficiency			>97.5%		
EU efficiency			>96.8%		
Protection					
Ground fault monitoring			Yes		
Integrated AFCI (DC arc-fault circuit protection)			Optional		
DC reverse-polarity protection			Yes		
Protection class/Over voltage category			I/II		
General Data					
Dimensions (W*H*D)			333*505*249 mm		
Weight			17kg		
Topology			High frequency isolation (for battery)		
Operating ambient temperature range			-25 ~ +60°C		
Ingress protecton/ Pollution degree			IP65/PD3		
Cooling concept			Natural convection		
Max. operation altitude			2000m		
Grid connection standard			EN50438, G98, G99, AS4777.2:2015, VDE0126-1-1, IEC 61727, VDE N4105, CEI 0-21,CE		
Safety/EMC standard			IEC62040-1, IEC62109-1/-2, AS3100, NB/T 32004, EN61000-6-2, EN61000-6-3		
Features					
DC connection			MC4 connector		
AC connection			Quick connection plug		
Display			7.0"LCD color screen display		
Communication			RS485, Optional: Wi-Fi, GPRS		